

C22M80 Information



For Reference Only

Part Number C22M80 Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 80A 500VAC NON STD

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









C22M80 Specifications

Manufacturer Part NumberC22M80ManufacturerEatonCategoryCircuit ProtectionElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesC22MFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC500VVoltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage120kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.874" Dia x 2.283" L (22.20mm x 58.00mm)		
CategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesC22MFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC500VVoltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage120kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.874" Dia x 2.283" L (22.20mm x 58.00mm)	Manufacturer Part Number	C22M80
Package Cartridge, Non-Standard Series C22M Fuse Type Cartridge Current Rating 80A Voltage Rating - AC 500V Voltage Rating - DC - Response Time - Applications Motor Protection Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 120kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension (228M) Cartridge, Non-Standard Cartridge, Non-Standard Size / Dimension (228M) Cartridge, Non-Standard Cartridge, Non-Standard Size / Dimension (228M) Cartridge, Non-Standard Cartridge, Non-Standard Size / Dimension (228M)	Manufacturer	Eaton
Package Cartridge, Non-Standard Series C22M Fuse Type Cartridge Current Rating 80A Voltage Rating - AC 500V Voltage Rating - DC - Response Time - Applications Motor Protection Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 120kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.874" Dia x 2.283" L (22.20mm x 58.00mm)	Category	Circuit Protection
SeriesC22MFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC500VVoltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage120kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.874" Dia x 2.283" L (22.20mm x 58.00mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating80AVoltage Rating - AC500VVoltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage120kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.874" Dia x 2.283" L (22.20mm x 58.00mm)	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC SooV Voltage Rating - DC Response Time Applications Motor Protection Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 80A 80A 80A 80A 80A 80A 80A 80	Series	C22M
Voltage Rating - AC Voltage Rating - DC Response Time - Applications Motor Protection Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 500V 500V 500V 500V 500V 500V 600 - Catridge, Non-Standard 5008 5	Fuse Type	Cartridge
Voltage Rating - DC Response Time - Applications Motor Protection Features - Class - Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension - 0.874" Dia x 2.283" L (22.20mm x 58.00mm)	Current Rating	80A
Response Time Applications Motor Protection Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension - Class - Cartridge, Non-Standard O.874" Dia x 2.283" L (22.20mm x 58.00mm)	Voltage Rating - AC	500V
Applications Motor Protection Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 120kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.874" Dia x 2.283" L (22.20mm x 58.00mm)	Voltage Rating - DC	-
Features - Class - Class - Coperating Temperature - Capacity @ Rated Voltage 120kA Holder Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.874" Dia x 2.283" L (22.20mm x 58.00mm)	Response Time	-
Class - Approvals - Coperating Temperature - Seraking Capacity @ Rated Voltage 120kA Holder Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.874" Dia x 2.283" L (22.20mm x 58.00mm)	Applications	Motor Protection
Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 120kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.874" Dia x 2.283" L (22.20mm x 58.00mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 120kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.874" Dia x 2.283" L (22.20mm x 58.00mm)	Class	-
Breaking Capacity @ Rated Voltage 120kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.874" Dia x 2.283" L (22.20mm x 58.00mm)	Approvals	-
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.874" Dia x 2.283" L (22.20mm x 58.00mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.874" Dia x 2.283" L (22.20mm x 58.00mm)	Breaking Capacity @ Rated Voltage	120kA
Size / Dimension 0.874" Dia x 2.283" L (22.20mm x 58.00mm)	Mounting Type	Holder
· · · · · · · · · · · · · · · · · · ·	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.874" Dia x 2.283" L (22.20mm x 58.00mm)
		Report errors?

C22M80 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

C22M80 Payment Methods



















C22M80 Shipping Methods













If you have any question about C22M80, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com