



C300K8R0E Information



For Reference Only

Part Number C300K8R0E
Manufacturer Ohmite
Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 8 OHM 10% 300W

Package Radial, Tubular

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









C300K8R0E Specifications

Manufacturer Part Number C300K8R0E Manufacturer Ohmite Category Resistors Package Radial, Tubular Series Corrib?280 Resistance 8 Ohms Tolerance ±10% Power (Watts) 300W Composition Wirewound Temperature Coefficient ±400ppm/°C Operating Temperature -55°C ~ 400°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 1.125" Dia x 8.500" L (28.58mm x 215.90mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	CSOOKOKOE Specifications	
CategoryResistorsPackageRadial, TubularSeriesCorrib?280Resistance8 OhmsTolerance±10%Power (Watts)300WCompositionWirewoundTemperature Coefficient±400ppm/°COperating Temperature-55°C ~ 400°CFeatures-Coating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension1.125" Dia x 8.500" L (28.58mm x 215.90mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Manufacturer Part Number	C300K8R0E
PackageRadial, TubularSeriesCorrib?280Resistance8 OhmsTolerance±10%Power (Watts)300WCompositionWirewoundTemperature Coefficient±400ppm/°COperating Temperature-55°C ~ 400°CFeatures-Coating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension1.125" Dia x 8.500" L (28.58mm x 215.90mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Manufacturer	Ohmite
PackageRadial, TubularSeriesCorrib?280Resistance8 OhmsTolerance±10%Power (Watts)300WCompositionWirewoundTemperature Coefficient±400ppm/°COperating Temperature-55°C ~ 400°CFeatures-Coating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension1.125" Dia x 8.500" L (28.58mm x 215.90mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Category	Resistors
SeriesCorrib?280Resistance8 OhmsTolerance±10%Power (Watts)300WCompositionWirewoundTemperature Coefficient±400ppm/°COperating Temperature-55°C ~ 400°CFeatures-Coating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension1.125" Dia x 8.500" L (28.58mm x 215.90mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-		Chassis Mount Resistors
Resistance8 OhmsTolerance±10%Power (Watts)300WCompositionWirewoundTemperature Coefficient±400ppm/°COperating Temperature-55°C ~ 400°CFeatures-Coating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension1.125" Dia x 8.500" L (28.58mm x 215.90mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Package	Radial, Tubular
Tolerance ±10% Power (Watts) 300W Composition Wirewound Temperature Coefficient ±400pm/°C Operating Temperature -55°C ~ 400°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 1.125" Dia x 8.500" L (28.58mm x 215.90mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Series	Corrib?280
Power (Watts) Composition Wirewound Temperature Coefficient ±400ppm/°C Operating Temperature -55°C ~ 400°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 1.125" Dia x 8.500" L (28.58mm x 215.90mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Resistance	8 Ohms
Composition Wirewound Temperature Coefficient ±400ppm/°C Operating Temperature -55°C ~ 400°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 1.125" Dia x 8.500" L (28.58mm x 215.90mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Tolerance	±10%
Temperature Coefficient ±400ppm/°C Operating Temperature -55°C ~ 400°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 1.125" Dia x 8.500" L (28.58mm x 215.90mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Power (Watts)	300W
Operating Temperature -55°C ~ 400°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 1.125" Dia x 8.500" L (28.58mm x 215.90mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate - Solder Lugs	Composition	Wirewound
Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 1.125" Dia x 8.500" L (28.58mm x 215.90mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Temperature Coefficient	±400ppm/°C
Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 1.125" Dia x 8.500" L (28.58mm x 215.90mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Operating Temperature	-55°C ~ 400°C
Mounting Feature Brackets (not included) Size / Dimension 1.125" Dia x 8.500" L (28.58mm x 215.90mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Features	-
Size / Dimension 1.125" Dia x 8.500" L (28.58mm x 215.90mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Coating, Housing Type	Vitreous Enamel Coated
Height - Seated (Max) Lead Style Package / Case Radial, Tubular Failure Rate -	Mounting Feature	Brackets (not included)
Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Size / Dimension	1.125" Dia x 8.500" L (28.58mm x 215.90mm)
Package / Case Radial, Tubular Failure Rate -	Height - Seated (Max)	-
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Radial, Tubular
Report errors?	Failure Rate	-
		Report errors?

C300K8R0E Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

C300K8R0E Payment Methods



















C300K8R0E Shipping Methods













If you have any question about C300K8R0E, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com