



## C315C512JAG5TA Information



For Reference Only

Part Number C315C512JAG5TA

ManufacturerKEMETCategoryCapacitors

Ceramic Capacitors

**Description** CAP CER 5100PF 250V C0G RADIAL

Package Radia

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# C315C512JAG5TA Specifications

Manufacturer Part Number         C315C512JAG5TA           Manufacturer         KEMET           Category         Capacitors           Package         Radial           Series         Goldmax, 300           Capacitance         5100pF           Tolerance         ±5%           Voltage - Rated         250V           Temperature Coefficient         C0G, NPO           Operating Temperature         -55°C ~ 125°C           Features         Low ESL           Ratings         -           Applications         Bypass, Decoupling           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Radial           Size / Dimension         0.150" L x 0.100" W (3.81mm x 2.54mm)           Height - Seated (Max)         0.183" (4.66mm)           Thickness (Max)         -           Lead Spacing         0.100" (2.54mm)           Lead Style         Straight		
Category         Capacitors           Package         Radial           Series         Goldmax, 300           Capacitance         5100pF           Tolerance         ±5%           Voltage - Rated         250V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         Low ESL           Ratings         -           Applications         Bypass, Decoupling           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Radial           Size / Dimension         0.150" L x 0.100" W (3.81mm x 2.54mm)           Height - Seated (Max)         0.183" (4.66mm)           Thickness (Max)         -           Lead Spacing         0.100" (2.54mm)           Lead Style         Straight	Manufacturer Part Number	C315C512JAG5TA
Package         Radial           Series         Goldmax, 300           Capacitance         5100pF           Tolerance         ±5%           Voltage - Rated         250V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         Low ESL           Ratings         -           Applications         Bypass, Decoupling           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Radial           Size / Dimension         0.150" L x 0.100" W (3.81mm x 2.54mm)           Height - Seated (Max)         0.183" (4.66mm)           Thickness (Max)         -           Lead Spacing         0.100" (2.54mm)           Lead Style         Straight	Manufacturer	KEMET
Package         Radial           Series         Goldmax, 300           Capacitance         5100pF           Tolerance         ±5%           Voltage - Rated         250V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         Low ESL           Ratings         -           Applications         Bypass, Decoupling           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Radial           Size / Dimension         0.150" L x 0.100" W (3.81mm x 2.54mm)           Height - Seated (Max)         0.183" (4.66mm)           Thickness (Max)         -           Lead Spacing         0.100" (2.54mm)           Lead Style         Straight	Category	Capacitors
Series         Goldmax, 300           Capacitance         5100pF           Tolerance         ±5%           Voltage - Rated         250V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         Low ESL           Ratings         -           Applications         Bypass, Decoupling           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Radial           Size / Dimension         0.150" L x 0.100" W (3.81mm x 2.54mm)           Height - Seated (Max)         0.183" (4.66mm)           Thickness (Max)         -           Lead Spacing         0.100" (2.54mm)           Lead Style         Straight		Ceramic Capacitors
Capacitance         5100pF           Tolerance         ±5%           Voltage - Rated         250V           Temperature Coefficient         C0G, NPO           Operating Temperature         -55°C ~ 125°C           Features         Low ESL           Ratings         -           Applications         Bypass, Decoupling           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Radial           Size / Dimension         0.150" L x 0.100" W (3.81mm x 2.54mm)           Height - Seated (Max)         0.183" (4.66mm)           Thickness (Max)         -           Lead Spacing         0.100" (2.54mm)           Lead Style         Straight	Package	Radial
Tolerance ±5%  Voltage - Rated 250V  Temperature Coefficient C0G, NP0  Operating Temperature -55°C ~ 125°C  Features Low ESL  Ratings - Applications Bypass, Decoupling  Failure Rate - Mounting Type Through Hole  Package / Case Radial  Size / Dimension 0.150" L x 0.100" W (3.81mm x 2.54mm)  Height - Seated (Max) 0.183" (4.66mm)  Thickness (Max) - Lead Spacing 0.100" (2.54mm)  Lead Style Straight	Series	Goldmax, 300
Voltage - Rated250VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.150" L x 0.100" W (3.81mm x 2.54mm)Height - Seated (Max)0.183" (4.66mm)Thickness (Max)-Lead Spacing0.100" (2.54mm)Lead StyleStraight	Capacitance	5100pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension Height - Seated (Max) Thickness (Max) - Lead Spacing Lead Style Straight	Tolerance	±5%
Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.150" L x 0.100" W (3.81mm x 2.54mm)Height - Seated (Max)0.183" (4.66mm)Thickness (Max)-Lead Spacing0.100" (2.54mm)Lead StyleStraight	Voltage - Rated	250V
Features  Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style Low ESL  Bypass, Decoupling Through Hole - University (Augustum of the Augustum of the Augu	Temperature Coefficient	C0G, NP0
Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.150" L x 0.100" W (3.81mm x 2.54mm) Height - Seated (Max) 0.183" (4.66mm) Thickness (Max) - Lead Spacing 0.100" (2.54mm) Lead Style Straight	Operating Temperature	-55°C ~ 125°C
Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.150" L x 0.100" W (3.81mm x 2.54mm) Height - Seated (Max) 0.183" (4.66mm) Thickness (Max) - Lead Spacing 0.100" (2.54mm) Lead Style Straight	Features	Low ESL
Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.150" L x 0.100" W (3.81mm x 2.54mm) Height - Seated (Max) 0.183" (4.66mm) Thickness (Max) - Lead Spacing 0.100" (2.54mm) Lead Style Straight	Ratings	-
Mounting Type  Package / Case  Radial  Size / Dimension  0.150" L x 0.100" W (3.81mm x 2.54mm)  Height - Seated (Max)  0.183" (4.66mm)  Thickness (Max)  -  Lead Spacing  0.100" (2.54mm)  Lead Style  Straight	Applications	Bypass, Decoupling
Package / Case Radial Size / Dimension 0.150" L x 0.100" W (3.81mm x 2.54mm) Height - Seated (Max) 0.183" (4.66mm)  Thickness (Max) - Lead Spacing 0.100" (2.54mm) Lead Style Straight	Failure Rate	-
Size / Dimension       0.150" L x 0.100" W (3.81mm x 2.54mm)         Height - Seated (Max)       0.183" (4.66mm)         Thickness (Max)       -         Lead Spacing       0.100" (2.54mm)         Lead Style       Straight	Mounting Type	Through Hole
Height - Seated (Max)  Thickness (Max)  Lead Spacing  Lead Style  0.183" (4.66mm)  -  Under Control of the seated (Max)  Under Control of the seated (Max)  Straight	Package / Case	Radial
Thickness (Max)  Lead Spacing  0.100" (2.54mm)  Lead Style  Straight	Size / Dimension	0.150" L x 0.100" W (3.81mm x 2.54mm)
Lead Spacing0.100" (2.54mm)Lead StyleStraight	Height - Seated (Max)	0.183" (4.66mm)
Lead Style Straight	Thickness (Max)	-
	Lead Spacing	0.100" (2.54mm)
Report errors?	Lead Style	Straight
		Report errors?

#### C315C512JAG5TA Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### C315C512JAG5TA Payment Methods



















## C315C512JAG5TA Shipping Methods













If you have any question about C315C512JAG5TA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com