



C315C622F3G5TA Information



For Reference Only

Part Number C315C622F3G5TA

Manufacturer KEMET Category Capacitors

Ceramic Capacitors

Description CAP CER 6200PF 25V C0G RADIAL

Package Radia

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









C315C622F3G5TA Specifications

Manufacturer Part Number C315C622F3G5TA Manufacturer KEMET Category Capacitors Package Radial Series Goldmax, 300 Capacitance 6200pF Tolerance ±1% Voltage - Rated 25V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.150" L x 0.100" W (3.81mm x 2.54mm)		
CategoryCapacitorsPackageRadialSeriesGoldmax, 300Capacitance6200pFTolerance±1%Voltage - Rated25VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadial	Manufacturer Part Number	C315C622F3G5TA
PackageRadialSeriesGoldmax, 300Capacitance6200pFTolerance±1%Voltage - Rated25VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadial	Manufacturer	KEMET
PackageRadialSeriesGoldmax, 300Capacitance6200pFTolerance±1%Voltage - Rated25VTemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadial	Category	Capacitors
Series Goldmax, 300 Capacitance 6200pF Tolerance ±1% Voltage - Rated 25V Temperature Coefficient COG, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Radial		Ceramic Capacitors
Capacitance6200pFTolerance±1%Voltage - Rated25VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadial	Package	Radial
Tolerance ±1% Voltage - Rated 25V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Radial	Series	Goldmax, 300
Voltage - Rated 25V Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Radial	Capacitance	6200pF
Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Radial	Tolerance	$\pm 1\%$
Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Radial	Voltage - Rated	25V
Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Radial	Temperature Coefficient	COG, NPO
Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Radial	Operating Temperature	-55°C ~ 125°C
Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Radial	Features	Low ESL
Failure Rate - Mounting Type Through Hole Package / Case Radial	Ratings	-
Mounting Type Through Hole Package / Case Radial	Applications	Bypass, Decoupling
Package / Case Radial	Failure Rate	-
	Mounting Type	Through Hole
Size / Dimension 0.150" L x 0.100" W (3.81mm x 2.54mm)	Package / Case	Radial
	Size / Dimension	0.150" L x 0.100" W (3.81mm x 2.54mm)
Height - Seated (Max) 0.183" (4.66mm)	Height - Seated (Max)	0.183" (4.66mm)
Thickness (Max) -	Thickness (Max)	-
Lead Spacing 0.100" (2.54mm)	Lead Spacing	0.100" (2.54mm)
Lead Style Straight	Lead Style	Straight
Report errors?		Report errors?

C315C622F3G5TA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

C315C622F3G5TA Payment Methods



















C315C622F3G5TA Shipping Methods













If you have any question about C315C622F3G5TA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com