

C317C152G2G5TA

Request a Quote

C317C152G2G5TA Information



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



C317C152G2G5TA Specifications

ManufacturerKEMETCategoryCapacitorsCeramic CapacitorsCeramic CapacitorsPackageRadialSeriesGoldmax, 300Capacitance1500pFFolerance±2%Voltage - Rated00VComperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CPactangs-ApplicationsBypass, DecouplingFailure Rate-ApplicationsThrough HolePackage / CaseRadialSize / Dimension0.150° L x 0.100° W (3.81mm x 2.54mm)		
CategoryCapacitorsCategoryCeramic CapacitorsPackageRadialPackageGoldmax, 300Capacitance1500pFColerance±2%Yoltage - Rated200VPorentificientCoG, NPOOperating Temperature-55°C ~ 125°CPactangsJours SLApplicationsBypass, DecouplingFailure Rate-Appleading TypeThrough HolePackage / CaseRatialSize / Dimension0.50° L x 0.100° W (3.81mm x 2.54mm)	Manufacturer Part Number	C317C152G2G5TA
Ceramic CapacitorsPackageRadialPackageGoldmax, 300Capacitance1500pFFolerance±2%Voltage - Rated200VComperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CValtagsLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Voltage - CaseRadialPackage / CaseCoupling Through HoleSize / Dimension0.150" L x 0.100" W (3.81mm x 2.54mm)	Manufacturer	KEMET
PackageRadialBeriesGoldmax, 300Capacitance1500pFFolerance±2%Voltage - Rated200VCemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CCaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Package / CaseRadialSize / Dimension0.150" L x 0.100" W (3.81mm x 2.54mm)	Category	Capacitors
Series Goldmax, 300 Capacitance 1500pF Folerance ±2% Voltage - Rated 200V Pemperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Aounting Type Through Hole Package / Case Radial Size / Dimension 0.150° L x 0.100° W(3.81mm x 2.54mm)		Ceramic Capacitors
Capacitance1500pFFolerance±2%Voltage - Rated200VFemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Volunting TypeThrough HolePackage / CaseRadialSize / Dimension0.150" L x 0.100" W (3.81mm x 2.54mm)	Package	Radial
Folerance±2%Folerance200VComperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CSeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.150" L x 0.100" W (3.81mm x 2.54mm)	Series	Goldmax, 300
Woltage - Rated200VCemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Aounting TypeThrough HolePackage / CaseRadialSize / Dimension0.150" L x 0.100" W (3.81mm x 2.54mm)	Capacitance	1500pF
Femperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Aounting TypeThrough HolePackage / CaseRadialSize / Dimension0.150" L x 0.100" W (3.81mm x 2.54mm)	Tolerance	±2%
Deperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.150" L x 0.100" W (3.81mm x 2.54mm)	Voltage - Rated	200V
FeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.150" L x 0.100" W (3.81mm x 2.54mm)	Temperature Coefficient	COG, NP0
Ratings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.150" L x 0.100" W (3.81mm x 2.54mm)	Operating Temperature	-55°C ~ 125°C
ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.150" L x 0.100" W (3.81mm x 2.54mm)	Features	Low ESL
Failure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.150" L x 0.100" W (3.81mm x 2.54mm)	Ratings	-
Mounting TypeThrough HolePackage / CaseRadialBize / Dimension0.150" L x 0.100" W (3.81mm x 2.54mm)	Applications	Bypass, Decoupling
Package / CaseRadialSize / Dimension0.150" L x 0.100" W (3.81mm x 2.54mm)	Failure Rate	-
Size / Dimension 0.150" L x 0.100" W (3.81mm x 2.54mm)	Mounting Type	Through Hole
	Package / Case	Radial
Height - Seated (Max)0.200" (5.08mm)	Size / Dimension	0.150" L x 0.100" W (3.81mm x 2.54mm)
	Height - Seated (Max)	0.200" (5.08mm)
Thickness (Max) -	Thickness (Max)	-
Lead Spacing 0.200" (5.08mm)	Lead Spacing	0.200" (5.08mm)
Lead Style Formed Leads - Kinked	Lead Style	Formed Leads - Kinked
Report errors?		Report errors?

C317C152G2G5TA Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

C317C152G2G5TA Payment Methods





If you have any question about C317C152G2G5TA, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com