

C317C161G3G5TA

Request a Quote

C317C161G3G5TA Information





Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



C317C161G3G5TA Specifications

Manufacturer Part NumberC317C161G3G5TAManufacturerKEMETCategoryCapacitorsCaramic CapacitorsCeramic CapacitorsPackageRadialCaractionsGoldmax, 300Capacitance±2%Yoltage - Rated25VPoperating Temperature-55°C ~ 125°CPacturesLow ESLRatings-ApplicationsBypass, DecouplingPailure Rate-Aunufing TypeThrough HolePackage / CaseRadialSize / Dimension0.150" L x 0.100" W (3.81mm x 2.54mm)
CategoryCapacitorsCaranic CapacitorsPackageRadialPackageGoldmax, 300Capacitance160pFColerance±2%Yoltage - Rated25VComperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CPactageLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Apple CaseThrough HolePackage / CaseRadial
Ceramic CapacitorsPackageRadialPackageGoldmax, 300Capacitance160pFPolerance±2%Voltage - Rated25VComperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CPactargsLow ESLRatings-ApplicationsBypass, DecouplingPackage / CaseRadial
PackageRadialPackageGoldmax, 300Capacitance160pFColerance±2%Yoltage - Rated25VComperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CPactargesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Package / CaseRadialPackage / CaseRadial
deriesGoldmax, 300Capacitance160pFColerance±2%Yoltage - Rated25VComperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CGeaturesLow ESLRatings-ApplicationsBypass, DecouplingGalure Rate-Aounting TypeThrough HolePackage / CaseRadial
Capacitance160pFColerance±2%Voltage - Rated25VComperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CCeaturesLow ESLRatings-ApplicationsBypass, DecouplingVoluting Type-Package / CaseRadial
Folerance±2%Yoltage - Rated25VYoltage - RatedCOG, NPOOperating Temperature-55°C ~ 125°CYeaturesLow ESLYeatures-ApplicationsBypass, DecouplingYalure Rate-Youting TypeThrough HolePackage / CaseRatial
Yoltage - Rated25VYemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CYeaturesLow ESLRatings-ApplicationsBypass, DecouplingYeature Rate-Younting TypeThrough HolePackage / CaseRadial
Comperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CSeaturesLow ESLRatings-ApplicationsBypass, DecouplingSailure Rate-Aounting TypeThrough HolePackage / CaseRadial
Deperating Temperature-55°C ~ 125°CSeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Aounting TypeThrough HolePackage / CaseRadial
SeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Aounting TypeThrough HolePackage / CaseRadial
Ratings-ApplicationsBypass, DecouplingFailure Rate-Aounting TypeThrough HolePackage / CaseRadial
ApplicationsBypass, DecouplingFailure Rate-Aounting TypeThrough HolePackage / CaseRadial
Failure Rate-Aounting TypeThrough HolePackage / CaseRadial
Mounting TypeThrough HolePackage / CaseRadial
Package / Case Radial
Dimension 0.150" L x 0.100" W (3.81mm x 2.54mm)
Height - Seated (Max) 0.200" (5.08mm)
Thickness (Max) -
Lead Spacing 0.200" (5.08mm)
Lead Style Formed Leads - Kinked
Report errors?

C317C161G3G5TA Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

C317C161G3G5TA Payment Methods





If you have any question about C317C161G3G5TA, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com