

# C317C180G3G5TA

**Request a Quote** 

### C317C180G3G5TA Information





Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## C317C180G3G5TA Specifications

Manufacturer Part Number C317C180G3G5TA   Manufacturer KEMET   Capacitors Ceramic Capacitors   ackage Radial   eries Goldmax, 300   Capacitance 18pF   Voltage - Rated 25V   Permetrature Coefficient C0G, NP0   Operating Temperature -55°C ~ 125°C   eatures Low ESL   eatures Sypass, Decoupling   atlare Rate -
CapacitorsCapacitorsCacamic CapacitorsackageRadialackageGoldmax, 300capacitance18pFolerance±2%voltage - Rated25Vcomperature CoefficientCOG, NP0operating Temperature-55°C ~ 125°CcaturesLow ESLcatures-applicationsBypass, Decouplingadure Rate-adure Rate- <tr< td=""></tr<>
Ceramic CapacitorsackageRadialeriesGoldmax, 300apacitance18pFolerance±2%voltage - Rated25Vcemperature CoefficientCOG, NPOoperating Temperature-55°C ~ 125°CeaturesLow ESLatings-atings-atings-atinge RateBypass, Decouplingatinge Rate-
ackageRadialeriesGoldmax, 300Capacitance18pFcolerance±2%Yoltage - Rated25VComperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CeaturesLow ESLcatings-seplicationsBypass, Decouplingaulure Rate-
Prime eriesGoldmax, 300Papacitance18pFPolerance±2%Polerance25VPolerature CoefficientCOG, NPOPoperating Temperature-55°C ~ 125°CPeaturesLow ESLPatings-PapilcationsBypass, DecouplingPating Rate-
Papacitance18pFPolerance±2%Poltage - Rated25VPemperature CoefficientCOG, NPOPoperating Temperature-55°C ~ 125°CPetaturesLow ESLPatings-PaplicationsBypass, DecouplingPating Rate-
Polerance±2%Poltage - Rated25VPomperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CPeteraturesLow ESLPatings-PuplicationsBypass, DecouplingPatine Rate-
Yoltage - Rated25VYemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CYeaturesLow ESLYeatings-ApplicationsBypass, DecouplingYalue Rate-
Permerature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CeaturesLow ESLatings-ApplicationsBypass, Decouplingailure Rate-
Operating Temperature-55°C ~ 125°CeaturesLow ESLatings-applicationsBypass, Decouplingailure Rate-
PeaturesLow ESLatings-applicationsBypass, Decouplingailure Rate-
atings-applicationsBypass, Decouplingailure Rate-
Applications Bypass, Decoupling ailure Rate -
ailure Rate -
Iounting Type Through Hole
ackage / Case Radial
ize / Dimension 0.150" L x 0.100" W (3.81mm x 2.54mm)
Leight - Seated (Max)   0.200" (5.08mm)
- hickness (Max)
ead Spacing 0.200" (5.08mm)
ead Style Formed Leads - Kinked
Report errors?

#### C317C180G3G5TA Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### C317C180G3G5TA Payment Methods





If you have any question about C317C180G3G5TA, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com