



C321C399C3G5TA Information

www.heisener.com

For Reference Only

Part Number C321C399C3G5TA

Manufacturer KEMET Category Capacitors

Ceramic Capacitors

Description CAP CER 3.9PF 25V C0G RADIAL

Package Radia

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









C321C399C3G5TA Specifications

Manufacturer Part NumberC321C399C3G5TAManufacturerKEMETCategoryCapacitorsPackageRadialSeriesGoldmax, 300Capacitance3.9pFTolerance±0.25pFVoltage - Rated25VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-
CategoryCapacitorsPackageRadialSeriesGoldmax, 300Capacitance3.9pFTolerance±0.25pFVoltage - Rated25VTemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-
PackageRadialSeriesGoldmax, 300Capacitance3.9pFTolerance±0.25pFVoltage - Rated25VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-
PackageRadialSeriesGoldmax, 300Capacitance3.9pFTolerance±0.25pFVoltage - Rated25VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-
Series Goldmax, 300 Capacitance 3.9pF Tolerance ±0.25pF Voltage - Rated 25V Temperature Coefficient COG, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate -
Capacitance3.9pFTolerance±0.25pFVoltage - Rated25VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-
Tolerance ±0.25pF Voltage - Rated 25V Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate -
Voltage - Rated25VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-
Temperature Coefficient COG, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate -
Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate -
Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate -
Ratings - Applications Bypass, Decoupling Failure Rate -
Applications Bypass, Decoupling Failure Rate -
Failure Rate -
Mounting Type Through Hole
Package / Case Radial
Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm)
Height - Seated (Max) 0.260" (6.60mm)
Thickness (Max)
Lead Spacing 0.250" (6.35mm)
Lead Style Formed Leads - Kinked
Report errors?

C321C399C3G5TA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

C321C399C3G5TA Payment Methods



















C321C399C3G5TA Shipping Methods













If you have any question about C321C399C3G5TA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com