



C322C201J3G5TA Information



For Reference Only

Part Number C322C201J3G5TA

Manufacturer KEMET Category Capacitors

Ceramic Capacitors

Description CAP CER 200PF 25V C0G RADIAL

Package Radia

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









C322C201J3G5TA Specifications

Manufacturer Part Number C322C201J3G5TA Manufacturer KEMET Category Capacitors Package Radial Series Goldmax, 300 Capacitance 200pF Tolerance ±5% Voltage - Rated 25V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm) Height - Seated (Max) 0.260" (6.60mm)		
CategoryCapacitorsPackageRadialSeriesGoldmax, 300Capacitance200pFTolerance±5%Voltage - Rated25 VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)	Manufacturer Part Number	C322C201J3G5TA
PackageRadialSeriesGoldmax, 300Capacitance200pFTolerance±5%Voltage - Rated25VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)	Manufacturer	KEMET
PackageRadialSeriesGoldmax, 300Capacitance200pFTolerance±5%Voltage - Rated25 VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)	Category	Capacitors
Series Goldmax, 300 Capacitance 200pF Tolerance ±5% Voltage - Rated 25V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm)		Ceramic Capacitors
Capacitance200pFTolerance±5%Voltage - Rated25VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)	Package	Radial
Tolerance ±5% Voltage - Rated 25V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm)	Series	Goldmax, 300
Voltage - Rated25VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)	Capacitance	200pF
Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension COG, NPO -04 -05°C -05°C -125°C -04 -04 -04 -05 -05 -05 -05 -05	Tolerance	±5%
Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension -55°C ~ 125°C Town ESL Low ESL - Ratings - Nounting Type Bypass, Decoupling Through Hole - County Hole Ratings Radial	Voltage - Rated	25V
Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm)	Temperature Coefficient	C0G, NP0
Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm)	Operating Temperature	-55°C ~ 125°C
Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm)	Features	Low ESL
Failure Rate Mounting Type Through Hole Package / Case Radial Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm)	Ratings	-
Mounting Type Through Hole Package / Case Radial Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm)	Applications	Bypass, Decoupling
Package / Case Radial Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm)	Failure Rate	-
Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm)	Mounting Type	Through Hole
	Package / Case	Radial
Height - Seated (Max) 0.260" (6.60mm)	Size / Dimension	0.200" L x 0.125" W (5.08mm x 3.18mm)
0.200 (0.00mm)	Height - Seated (Max)	0.260" (6.60mm)
Thickness (Max) -	Thickness (Max)	-
Lead Spacing 0.200" (5.08mm)	Lead Spacing	0.200" (5.08mm)
Lead Style Formed Leads - Kinked	Lead Style	Formed Leads - Kinked
Report errors?		Report errors?

C322C201J3G5TA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

C322C201J3G5TA Payment Methods



















C322C201J3G5TA Shipping Methods













If you have any question about C322C201J3G5TA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com