

C322C242FAG5TA

Request a Quote

C322C242FAG5TA Information

	Part Number	C322C242FAG5TA
	Manufacturer	KEMET
www.heisener.com	Category	Capacitors Ceramic Capacitors
	Description	CAP CER 2400PF 250V C0G RADIAL
	Package	Radial
		For the pricing/inventory/lead time, please contact
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



C322C242FAG5TA Specifications

ManufacturerKEMETCacacitorsPackageCaramic CapacitorsPackageRadialSeriesGoldmax, 300Capacitance2400pFTolerance±1%Voltage - Rated250VTomperature CoefficientCOG, NP0Operating Temperature55°C ~ 125°CPattings-ApplicationsBypass, DecouplingFailure Rate-ApplicationsSingenseFailure Rate-Mounting TypeHolePackage / CaseRadialSize / Dimension0.200° Lx 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)0.200° (6.60mm)Lead Spacing0.200° (5.08mm)	-		
CategoryCapacitorsPackageRadialPackageRadialSeriesGoldmax, 300Capacitance2400pFTolerance±1%Voltage - Rated250VCorperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CPattings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)6.200° L s 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)0.200° L x 0.125° W (5.08mm x 3.18mm)	Manufacturer Part Number	C322C242FAG5TA	
Ceramic CapacitorsPackageRadialSeriesGoldmax, 300Capacitance2400pFTolerance±1%Voltage - Rated250VCoperating Temperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing6.0200° (5.08mm)Lead StyleFormed Leads - Kinked	Manufacturer	KEMET	
PackageRadialSeriesGoldmax, 300Capacitance2400pFTolerance±1%Voltage - Rated250VTomperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Nounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing6.200° (5.08mm)Lead StyleFormed Leads - Kinked	Category	Capacitors	
Series Goldmax, 300 Capacitance 2400pF Tolerance ±1% Voltage - Rated 250V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Nounting Type Through Hole Package / Case Radial Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing 0.200" (5.08mm) Lead Style Formed Leads - Kinked		Ceramic Capacitors	
Capacitance2400pFTolerance±1%Voltage Rated250VTemperature CoefficientCOG, NPOOperating Temperature-5°C ~ 125°CPeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200° (5.08mm)Lead StyleFormed Leads - Kinked	Package	Radial	
Tolerance±1%Voltage - Rated250VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead StyleFormed Leads - Kinked	Series	Goldmax, 300	
Voltage - Rated250VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200° (5.08mm)Lead StyleFormed Leads - Kinked	Capacitance	2400pF	
Temperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Tolerance	$\pm 1\%$	
Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Voltage - Rated	250V	
FeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.260" (6.60mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Temperature Coefficient	C0G, NP0	
Ratings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.260" (6.60mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Operating Temperature	-55°C ~ 125°C	
ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.260" (6.60mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Features	Low ESL	
Failure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.260" (6.60mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Ratings	-	
Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.260" (6.60mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Applications	Bypass, Decoupling	
Package / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.260" (6.60mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Failure Rate	-	
Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm) Height - Seated (Max) 0.260" (6.60mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm) Lead Style Formed Leads - Kinked	Mounting Type	Through Hole	
Height - Seated (Max)0.260" (6.60mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Package / Case	Radial	
Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Size / Dimension	0.200" L x 0.125" W (5.08mm x 3.18mm)	
Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Height - Seated (Max)	0.260" (6.60mm)	
Lead Style Formed Leads - Kinked	Thickness (Max)	-	
	Lead Spacing	0.200" (5.08mm)	
Report errors?	Lead Style	Formed Leads - Kinked	
		Report errors?	

C322C242FAG5TA Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

C322C242FAG5TA Payment Methods



C322C242FAG5TA Shipping Methods



If you have any question about C322C242FAG5TA, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com