



C322C752FAG5TA Information

www.heisener.com

For Reference Only

Part Number C322C752FAG5TA

Manufacturer KEMET Category Capacitors

Ceramic Capacitors

Description CAP CER 7500PF 250V C0G RADIAL

Package Radia

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









C322C752FAG5TA Specifications

Manufacturer Part Number C322C752FAG5TA Manufacturer KEMET Category Capacitors Package Radial Series Goldmax, 300 Capacitance 7500pF Tolerance ±1% Voltage - Rated 250V Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm) Height - Seated (Max) 0.260" (6.60mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm) Lead Style Formed Leads - Kinked		
Category Capacitors Package Radial Series Goldmax, 300 Capacitance 7500pF Tolerance ±1% Voltage - Rated 250V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm) Height - Seated (Max) 0.260" (6.60mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm)	Manufacturer Part Number	C322C752FAG5TA
Package Radial Series Goldmax, 300 Capacitance 7500pF Tolerance ±1% Voltage - Rated 250V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm) Height - Seated (Max) 0.260" (6.60mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm)	Manufacturer	KEMET
Package Radial Series Goldmax, 300 Capacitance 7500pF Tolerance ±1% Voltage - Rated 250V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm) Height - Seated (Max) 0.260" (6.60mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm)	Category	Capacitors
Series Goldmax, 300 Capacitance 7500pF Tolerance ±1% Voltage - Rated 250V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm) Height - Seated (Max) 0.260" (6.60mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm)		Ceramic Capacitors
Capacitance 7500pF Tolerance ±1% Voltage - Rated 250V Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm) Height - Seated (Max) 0.260" (6.60mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm)	Package	Radial
Tolerance ±1% Voltage - Rated 250V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm) Height - Seated (Max) 0.260" (6.60mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm)	Series	Goldmax, 300
Voltage - Rated Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm) Height - Seated (Max) Thickness (Max) - Lead Spacing 0.200" (5.08mm)	Capacitance	7500pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate Mounting Type Through Hole Package / Case Radial Size / Dimension O.200" L x 0.125" W (5.08mm x 3.18mm) Height - Seated (Max) Thickness (Max) - Lead Spacing COG, NPO COG, NPO COG, NPO Low ESL Awa ESL Awa ESL Awa ESL Company Company	Tolerance	±1%
Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.260" (6.60mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)	Voltage - Rated	250V
Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm) Height - Seated (Max) 0.260" (6.60mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm)	Temperature Coefficient	C0G, NP0
Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm) Height - Seated (Max) 0.260" (6.60mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm)	Operating Temperature	-55°C ~ 125°C
Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm) Height - Seated (Max) 0.260" (6.60mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm)	Features	Low ESL
Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm) Height - Seated (Max) 0.260" (6.60mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm)	Ratings	-
Mounting Type Through Hole Package / Case Radial Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm) Height - Seated (Max) 0.260" (6.60mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm)	Applications	Bypass, Decoupling
Package / Case Radial Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm) Height - Seated (Max) 0.260" (6.60mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm)	Failure Rate	-
Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm) Height - Seated (Max) 0.260" (6.60mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm)	Mounting Type	Through Hole
Height - Seated (Max) 0.260" (6.60mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm)	Package / Case	Radial
Thickness (Max) Lead Spacing - 0.200" (5.08mm)	Size / Dimension	0.200" L x 0.125" W (5.08mm x 3.18mm)
Lead Spacing 0.200" (5.08mm)	Height - Seated (Max)	0.260" (6.60mm)
	Thickness (Max)	-
Lead Style Formed Leads - Kinked	Lead Spacing	0.200" (5.08mm)
	Lead Style	Formed Leads - Kinked
Report errors?		Report errors?

C322C752FAG5TA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

C322C752FAG5TA Payment Methods





















C322C752FAG5TA Shipping Methods













If you have any question about C322C752FAG5TA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com