

C322C821F3G5TA

C322C821F3G5TA Information



ıber	C322C821F3G5TA
turer	KEMET
	Capacitors Ceramic Capacitors
on	CAP CER 820PF 25V COG RADIAL
	Radial
	For the pricing/inventory/lead time, please contact
	us
	Website: https://www.heisener.com
	E-mail: salesdept@heisener.com



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



C322C821F3G5TA Specifications

Manufacturer Part Number C322C821F3G5TA Manufacturer KEMET Category Capacitors Category Ceramic Capacitors Package Radial Series Goldmax, 300 Capacitance 820pF Tolerance ±1% Voltage - Rated 25V Operating Temperature CoG, NP0 Operating Temperature coS°C ~ 125°C Pachage Low ESL Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Size / Dimension 0.200° L x 0.125° W (5.08mm x 3.18mm) Height - Seated (Max) 0.200° (6.60mm) Thickness (Max) - Lead Spacing 0.200° (5.08mm x 3.18mm)		
CategoryCapacitorsPackageRadialSeriesGoldmax, 300Capacitance820pFTolerance±1%Voltage - RatedSVPorperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CRatings-6000000000000000000000000000000000000	Manufacturer Part Number	C322C821F3G5TA
Indext of the section of the sectio	Manufacturer	KEMET
PackageRadialSeriesGoldmax, 300Capacitance820pFTolerance±1%Voltage - Rated25VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Nounting TypeRadialSize / Dimension0.200° L x 0.125° W (5.08mm x 3.18mm)Fickers (Max)0.200° L x 0.125° W (5.08mm x 3.18mm)Fickers (Max)0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)0.200° (6.60mm)Fickers (Max)-Lead Spacing0.200° (5.08mm)Lead StyleFormed Leads - Kinked	Category	Capacitors
Constraint Goldmax, 300 Capacitance 820pF Tolerance ±1% Voltage - Rated 25V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Nounting Type Through Hole Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing 0.200" (5.08mm) Lead Style Formed Leads - Kinked		Ceramic Capacitors
Capacitance820pFTolerance±1%Voltage - Rated25VTemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HoleSize / Dimension0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200° (5.08mm)Lead StyleFormed Leads - Kinked	Package	Radial
Tolerance±1%Voltage - Rated25VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypas, DecouplingFailure Rate-Mounting TypeThrough HoleStackeg / CaseRadialSize / Dimension0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)-Lead Spacing0.200° (5.08mm)Lead StyleFormed Leads - Kinked	Series	Goldmax, 300
Voltage - Rated25VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFaiture Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)-Height Seated (Max)-Lead Spacing6.200° (5.08mm)Head StyleSourd (5.08mm)Head StyleFormed Leads - Kinked	Capacitance	820pF
Temperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)0.200° (6.60mm)Lead Spacing0.200° (5.08mm)Lead SpacingFormed Leads - Kinked	Tolerance	±1%
Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Voltage - Rated	25V
FeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadiaSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleSize / Size / S	Temperature Coefficient	C0G, NP0
Ratings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.260" (6.60mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leades - Kinked	Operating Temperature	-55°C ~ 125°C
ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.260" (6.60mm)Thickness (Max)0.200" (5.08mm)Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Features	Low ESL
Failure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.260" (6.60mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Ratings	-
Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.260" (6.60mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Applications	Bypass, Decoupling
Package / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.260" (6.60mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Failure Rate	-
Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm) Height - Seated (Max) 0.260" (6.60mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm) Lead Style Formed Leads - Kinked	Mounting Type	Through Hole
Height - Seated (Max)0.260" (6.60mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Package / Case	Radial
Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Size / Dimension	0.200" L x 0.125" W (5.08mm x 3.18mm)
Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Height - Seated (Max)	0.260" (6.60mm)
Lead Style Formed Leads - Kinked	Thickness (Max)	-
	Lead Spacing	0.200" (5.08mm)
Report errors?	Lead Style	Formed Leads - Kinked
		Report errors?

C322C821F3G5TA Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

C322C821F3G5TA Payment Methods





If you have any question about C322C821F3G5TA, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com