

C323C110F3G5TA

C323C110F3G5TA Information



Part Number	C323C110F3G5TA
Manufacturer	KEMET
Category	Capacitors Ceramic Capacitors
Description	CAP CER 11PF 25V COG RADIAL
Package	Radial
	For the pricing/inventory/lead time, please contact
	us
	Website: https://www.heisener.com
	E-mail: salesdept@heisener.com



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



C323C110F3G5TA Specifications

ManufacturerKEMETCategoryCapacitorsPackageRadialPackageGoldmax, 300Capacitance11pFTolerance±1%Voltage - Rated25VCoperating Temperature CoefficientCOG, NP0Operating Semes-55°C ~ 125°CRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0,200° (L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)6.200° (S.08mm)Lead Spacing0,200° (S.08mm)		
CategoryCapacitorsPackageRadialPackageGoldmax, 300Capacitance11pFColacacitance±1%Voltage - Rated25VCoperating Temperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CPattings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max).Height - Seated (Max).Thickness (Max).Lead Spacing0.200° (5.08mm)	Manufacturer Part Number	C323C110F3G5TA
Ceramic CapacitorsPackageRadialSeriesGoldmax, 300Capacitance11pFTolerance±1%Voltage - Rated25VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200° (5.08mm)	Manufacturer	KEMET
PackageRadialSeriesGoldmax, 300Capacitance11pFTolerance±1%Voltage - Rated25VTemperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Lead Spacing0.200" (5.08mm)	Category	Capacitors
Series Goldmax, 300 Capacitance 11pF Tolerance ±1% Voltage - Rated 25V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing 0.200" (5.08mm)		Ceramic Capacitors
Capacitance11pFTolerance±1%Voltage - Rated25VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Lead Spacing0.200" (5.08mm)	Package	Radial
Tolerance±1%Voltage - Rated25VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Lead Spacing0.200" (5.08mm)	Series	Goldmax, 300
Voltage - Rated25VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)	Capacitance	11pF
Temperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)	Tolerance	±1%
Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)	Voltage - Rated	25V
FeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)	Temperature Coefficient	C0G, NP0
Ratings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.300" (7.62mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)	Operating Temperature	-55°C ~ 125°C
ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.300" (7.62mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)	Features	Low ESL
Failure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.300" (7.62mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)	Ratings	-
Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.300" (7.62mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)	Applications	Bypass, Decoupling
Package / Case Radial Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm) Height - Seated (Max) 0.300" (7.62mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm)	Failure Rate	-
Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm) Height - Seated (Max) 0.300" (7.62mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm)	Mounting Type	Through Hole
Height - Seated (Max) 0.300" (7.62mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm)	Package / Case	Radial
Thickness (Max) - Lead Spacing 0.200" (5.08mm)	Size / Dimension	0.200" L x 0.125" W (5.08mm x 3.18mm)
Lead Spacing 0.200" (5.08mm)	Height - Seated (Max)	0.300" (7.62mm)
	Thickness (Max)	-
Lead Style Formed Leads - Kinked	Lead Spacing	0.200" (5.08mm)
	Lead Style	Formed Leads - Kinked
Report errors?		Report errors?

C323C110F3G5TA Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

C323C110F3G5TA Payment Methods



C323C110F3G5TA Shipping Methods



If you have any question about C323C110F3G5TA, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com