

C323C112F3G5TA

C323C112F3G5TA Information



Part Number	C323C112F3G5TA	
Manufacturer	KEMET	
Category	Capacitors Ceramic Capacitors	
Description	CAP CER 1100PF 25V COG RADIAL	
Package	Radial	
	For the pricing/inventory/lead time, please contact	
	us	
	Website: https://www.heisener.com	
	E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



C323C112F3G5TA Specifications

Manufacturer Part Number C332C112F3G5TA Manufacturer KEMET Category Capacitors Ceramic Capacitors Ceramic Capacitors Package Radial Series Goldmax, 300 Capacitance 1100pF Tolerance ±1% Voltage - Rated 25V Operating Temperature Coefficient 00G, NP0 Operating Temperature 55°C ~ 125°C Factures Low ESL Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Size / Dimension 0,200° L x 0.125° W (5.08mm x 3.18mm) Size / Dimension 0,300° (7.62mm) Thickness (Max) - Lead Spacing 0,200° (5.08mm)		
CategoryCapacitorsPackageRadialSeriesGoldmax, 300Capacitance1100pFTolerance±1%Voltage - RatedSovPorperature CoefficientCog, NP0Operating Temperature-55°C ~ 125°CPattersLow ESLRatings-ApplicationsJpas, DecouplingFailure Rate-Nourting TypeNong HolePackage / CaseRadialSize / Dimension.020°T x 0.125°W (5.08mm x 3.18mm)Faiters (Max).030°T (7.62mm)Faiters (Max).030°T (7.62mm)Faiters (Max).020°T (5.08mm x 3.18mm)Faiter Stater (Manufacturer Part Number	C323C112F3G5TA
Indext of the section of the sectio	Manufacturer	KEMET
PackageRadialSeriesGoldmax, 300Capacitance1100pFTolerance±1%Voltage - Rated25VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeRadialSize / Dimension0.200° L x 0.125° W (5.08mm x 3.18mm)Fickess (Max)-Height - Seated (Max)0.300° (7.62mm)Height - Seated (Max)-Lead Spacing0.200° L 0.015° M (5.08mm x 3.18mm)Height Seated (Max)-Height - Seated (Max)-Height Seated (Max)- <t< td=""><td>Category</td><td>Capacitors</td></t<>	Category	Capacitors
Constraint Goldmax, 300 Capacitance 1100pF Tolerance ±1% Voltage - Rated 25V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypas, Decoupling Failure Rate - Nounting Type Through Hole Size / Dimension 0.200° L x 0.125° W (5.08mm x 3.18mm) Height - Seated (Max) - Height - Seated (Max) 0.300° (7.62mm) Thickness (Max) - Lead Spacing 0.200° (5.08mm) Lead Style Formed Leads - Kinked		Ceramic Capacitors
Capacitance1100pFTolerance±1%Voltage - Rated25VTemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HoleSize / Dimension0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200° (5.08mm)Lead StyleFormed Leads - Kinked	Package	Radial
Tolerance±1%Voltage - Rated25VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HoleSize / Dimension0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)-Hoick (Max)-Lead Spacing-Lead Style0.200° (5.08mm)Height - Seated (Max)-Height - Seated (M	Series	Goldmax, 300
Voltage - Rated25VTemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)0.200° (5.08mm)Lead SpacingSour (5.08mm)Lead SyleFormed Leads - Kinked	Capacitance	1100pF
Temperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200° (5.08mm)Lead StyleFormed Leads - Kinked	Tolerance	±1%
Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Voltage - Rated	25V
FeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadiaSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)Height - Seated (Max)-Fickness (Max)-Fickness (Max)-Height - Seated (Max)-Start (Max)-Height - Seated (Max)-Start (Max)-Start (Max)-Height - Seated (Max)-Start (Max)-Height - Seated (Max)-Start (Max)- <t< td=""><td>Temperature Coefficient</td><td>C0G, NP0</td></t<>	Temperature Coefficient	C0G, NP0
Ratings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Operating Temperature	-55°C ~ 125°C
ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.300" (7.62mm)Thickness (Max)0.200" (5.08mm)Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Features	Low ESL
Failure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.300" (7.62mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Ratings	-
Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.300" (7.62mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Applications	Bypass, Decoupling
Package / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.300" (7.62mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Failure Rate	-
Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm) Height - Seated (Max) 0.300" (7.62mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm) Lead Style Formed Leads - Kinked	Mounting Type	Through Hole
Height - Seated (Max)0.300" (7.62mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Package / Case	Radial
Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Size / Dimension	0.200" L x 0.125" W (5.08mm x 3.18mm)
Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Height - Seated (Max)	0.300" (7.62mm)
Lead Style Formed Leads - Kinked	Thickness (Max)	-
	Lead Spacing	0.200" (5.08mm)
Report errors?	Lead Style	Formed Leads - Kinked
		Report errors?

C323C112F3G5TA Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

C323C112F3G5TA Payment Methods



C323C112F3G5TA Shipping Methods



If you have any question about C323C112F3G5TA, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com