

C324C820F3G5TA

C324C820F3G5TA Information



C324C820F3G5TA
KEMET
Capacitors Ceramic Capacitors
CAP CER 82PF 25V C0G RADIAL
Radial
For the pricing/inventory/lead time, please contact
us
Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



C324C820F3G5TA Specifications

Manufacturer Part Number C324C820F3G5TA Manufacturer KEMET Capacitors Capacitors Caramic Capacitors Ceramic Capacitors Package Radial Series Goldmax, 300 Capacitance 82pF Folerance ±1% Voltage - Rated 25V Premperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate -
CategoryCapacitorsCaranic CapacitorsPackageRadialPackageGoldmax, 300Capacitance82pFColerance±1%Voltage - Rated25VComperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypas, Decoupling
Ceramic CapacitorsPackageRadialPackageGoldmax, 300Capacitance82pFFolerance±1%Voltage - Rated25VSemperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CSeaturesLow ESLRatings-ApplicationsBypass, Decoupling
PackageRadialPackageGoldmax, 300Capacitance82pFFolerance±1%Voltage - Rated25VCemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CPactangs-Ratings-ApplicationsBypass, Decoupling
SeriesGoldmax, 300Capacitance82pFFolerance±1%Voltage - Rated25VFemperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, Decoupling
Capacitance82pFColerance±1%Yoltage - Rated25VComperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CSeaturesLow ESLRatings-ApplicationsBypass, Decoupling
Folerance±1%Yoltage - Rated25VFemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, Decoupling
Voltage - Rated25VCemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CSeaturesLow ESLRatings-ApplicationsBypass, Decoupling
Femperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, Decoupling
Deperating Temperature-55°C ~ 125°CGeaturesLow ESLRatings-ApplicationsBypass, Decoupling
FeaturesLow ESLRatings-ApplicationsBypass, Decoupling
Ratings-ApplicationsBypass, Decoupling
Applications Bypass, Decoupling
lailura Data
Mounting Type Through Hole
Package / Case Radial
Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm)
Height - Seated (Max)0.230" (5.84mm)
Lead Spacing 0.100" (2.54mm)
Lead Style Formed Leads - Kinked
Report errors?

C324C820F3G5TA Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

C324C820F3G5TA Payment Methods





If you have any question about C324C820F3G5TA, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com