

C325C339B3G5TA

C325C339B3G5TA Information

Heisener.com	Part Number Manufacturer Category Description Package		
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



C325C339B3G5TA Specifications

ManfacturerKEMETCapacitorsCapacitorsPackageRadialPackageGoldmax, 300Capacitance3.3pFColarace±0.1pFVoltage - RatedCOG, NPOPerenture CoefficientCOG, NPOOperating TemperatureSo°c ~ 125°CPactanceLow ESLPactanceSynaps, DecouplingFailure Rate-Package / CaseRatialPackage / CaseRatialPackage / CaseSioo" 1 x 0.125" W (5.08mm x 3.18mm)Package / CaseSize / DimensionHeight - Seated (Max)Chickness (Max)Lead SpacingLead SpacingLead StyleFormed Leads - Kinked		
CategoryCapacitorsPackageRadialPackageGoldmax, 300Capacitance3.3pFColerance±0.1pFVoltage - Rated25VPoperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CPacturesLow ESLApplicationsBypass, DecouplingPailure Rated-Applications0.200° L x 0.125°W (5.08mm x 3.18mm)Package / Case0.200° L x 0.125°W (5.08mm x 3.18mm)Package / Case0.300° (7.62mm)Etight - Seated (Max)0.200° (5.08mm)Chickness (Max)0.200° (5.08mm)Lead StyleFormed Leads - Kinked	Manufacturer Part Number	C325C339B3G5TA
Caranic CapacitorsPackageRadialPackageGoldmax, 300Capacitance3.3pFColerance±0.1pFVoltage - Rated25VPemperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CPeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Package / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Size / Dimension-Height - Seated (Max)-Charles (Max)-Lead Spacing0.200" (5.08mm)Lead Spacing0.200" (5.08mm)	Manufacturer	KEMET
PackageRadialSeriesGoldmax, 300Capacitance3.3pFFolerance±0.1pFVoltage - Rated25VTemperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Voltage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Chickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Category	Capacitors
Constraint Goldmax, 300 Capacitance 3.3pF Folerance ±0.1pF Voltage - Rated 25V Fomperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm) Height - Seated (Max) - Chickness (Max) - Lead Spacing 0.200" (5.08mm) Lead Syle Formed Leads - Kinked		Ceramic Capacitors
Capacitance3.3pFColparace±0.1pFVoltage - Rated25VFemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CCeaturesLow ESLRatings-ApplicationsBypass, DecouplingPackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Size / Dimension0.300" (7.62mm)Height - Seated (Max)-Chickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Package	Radial
Folerance±0.1pFVoltage - Rated25VPemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Fhickness (Max)-Lead Spaing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Series	Goldmax, 300
Voltage - Rated25VFemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Fhickness (Max)0.200" (5.08mm)Lead SpacingDiremed Leads - Kinked	Capacitance	3.3pF
Femperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Fhickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Tolerance	±0.1pF
Deperating Temperature-55°C ~ 125°CPeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Fhickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Voltage - Rated	25V
FractionLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.300" (7.62mm)Fhickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Temperature Coefficient	C0G, NP0
Ratings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Fhickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Operating Temperature	-55°C ~ 125°C
ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialPackage / Case0.200" L x 0.125" W (5.08mm x 3.18mm)Beight - Seated (Max)0.300" (7.62mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Features	Low ESL
Failure Rate-Mounting TypeThrough HolePackage / CaseRadialPackage / Case0.200" L x 0.125" W (5.08mm x 3.18mm)Bize / Dimension0.300" (7.62mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Ratings	-
Mounting TypeThrough HolePackage / CaseRadialPackage / Case0.200" L x 0.125" W (5.08mm x 3.18mm)Size / Dimension0.200" (7.62mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Applications	Bypass, Decoupling
Package / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.300" (7.62mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Failure Rate	-
Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm) Height - Seated (Max) 0.300" (7.62mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm) Lead Style Formed Leads - Kinked	Mounting Type	Through Hole
Height - Seated (Max)0.300" (7.62mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Package / Case	Radial
Fhickness (Max) - Lead Spacing 0.200" (5.08mm) Lead Style Formed Leads - Kinked	Size / Dimension	0.200" L x 0.125" W (5.08mm x 3.18mm)
Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Height - Seated (Max)	0.300" (7.62mm)
Lead Style Formed Leads - Kinked	Thickness (Max)	-
·	Lead Spacing	0.200" (5.08mm)
	Lead Style	Formed Leads - Kinked
Report errors?		Report errors?

C325C339B3G5TA Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

C325C339B3G5TA Payment Methods





If you have any question about C325C339B3G5TA, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com