

# C325C822F2G5TA

#### C325C822F2G5TA Information

Heisener.com	Part Number Manufacturer Category Description Package	C325C822F2G5TA KEMET Capacitors Ceramic Capacitors CAP CER 8200PF 200V C0G RADIAL Radial For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### C325C822F2G5TA Specifications

Manufacturer Part Number C332C822F2G5TA   Manufacturer KEMET   Category Capacitors   Caranic Capacitors Ceranic Capacitors   Package Radial   Series Goldmax, 300   Capacitance ±1%   Yoltage - Rated 200V   Operating Coefficient 00G, NP0   Operating Temperature Coefficient 00G, NP0   Patters Low ESL   Applications spacescape   Applications Bypass, Decoupling   Failure Rate -   Mounting Type Micro Yu Sto	•	
CategoryCapacitorsPackageRadialSeriesGoldmax, 300Capacitance8200pFTolerance±1%Voltage - Rated00VTomperature CoefficientCoG, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsSpass, DecouplingFailure Rate-Mounting TypeInfough HoleFackage / CaseRadialSize / Dimension.020°T x 0.125°W (5.08mm x 3.18mm)Fickers (Max).030°T (7.62mm)Height - Seated (Max).Height - Seated (Max).Size / Dimension.Height - Seated (Max).Height - Seated (Max).Height - Seated (Max).Lead SpacingLow (5.08mm)Lead Spacing.Lead StyleFormed Leads - Kinked	Manufacturer Part Number	C325C822F2G5TA
Indext of the seriesCeramic CapacitorsPackageRadialSeriesGoldmax, 300Capacitance£200pFTolerance±1%Voltage - Rated00VTemperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)-Height Seated (Max)-Lead Spacing6.200° (5.08mm)Lead Spacing6.200° (5.08mm)Lead StyleFormed Leads - Kinked	Manufacturer	KEMET
PackageRadialSeriesGoldmax, 300Capacitance8200pFTolerance±1%Voltage - Rated200VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeRadialSize / Dimension0.200° L x 0.125° W (5.08mm x 3.18mm)Fielder Max.300° (7.62mm)Height - Seated (Max).300° (7.62mm)Ficadsparing.200° L S0.151° W (5.08mm x 3.18mm)Height - Seated (Max).200° (5.08mm)Fielder Size / Dimension.200° (5.	Category	Capacitors
Series Goldmax, 300   Capacitance 8200pF   Tolerance ±1%   Voltage - Rated 200V   Temperature Coefficient COG, NP0   Operating Temperature -55°C ~ 125°C   Features Low ESL   Ratings -   Applications Bypas, Decoupling   Failure Rate -   Nounting Type Through Hole   Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm)   Size / Dimension -   Height - Seated (Max) -   Thickness (Max) -   Lead Spacing 0.200" (5.08mm)   Lead Spacing 0.200" (5.08mm)		Ceramic Capacitors
Capacitance8200pFTolerance±1%Voltage - Rated200VTemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HoleSize / Dimension0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)0.200° (5.08mm)Lead SpacingD.200° (5.08mm)Lead StyleFormed Leads - Kinked	Package	Radial
Tolerance±1%Voltage - Rated200VTemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypas, DecouplingFaiture Rate-Mounting TypeRadialPackage / CaseRadialSize / Dimension0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)-Hickness (Max)-Lead Spacing0.200° (5.08mm)Lead SpacingSize / Size	Series	Goldmax, 300
Voltage - Rated200VTemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)0.200° (5.08mm)Lead SpacingDireme Leads - Kinked	Capacitance	8200pF
TemperatureCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200° (5.08mm)Lead StyleFormed Leads - Kinked	Tolerance	±1%
Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Voltage - Rated	200V
FeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)Height - Seated (Max)-Size / Dimension-Fickness (Max)-Fickness (Max)-Start (Start)-Start (Start)-S	Temperature Coefficient	C0G, NP0
Ratings-ApplicationsBypas, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)Height - Seated (Max)-Start - Seated (Max)-Height - Seated (Max)-Height - Seated (Max)-Start - Seated (Max)-Height - Seated (Max)-Start - Seated (Max)-Start - Seated (Max)-Height - Seated (Max)-Start - Seated (Max)- <td>Operating Temperature</td> <td>-55°C ~ 125°C</td>	Operating Temperature	-55°C ~ 125°C
ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.300" (7.62mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Features	Low ESL
Failure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.300" (7.62mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Ratings	-
Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.300" (7.62mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Applications	Bypass, Decoupling
Package / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.300" (7.62mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Failure Rate	-
Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm)   Height - Seated (Max) 0.300" (7.62mm)   Thickness (Max) -   Lead Spacing 0.200" (5.08mm)   Lead Style Formed Leads - Kinked	Mounting Type	Through Hole
Height - Seated (Max)0.300" (7.62mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Package / Case	Radial
Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Size / Dimension	0.200" L x 0.125" W (5.08mm x 3.18mm)
Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Height - Seated (Max)	0.300" (7.62mm)
Lead Style Formed Leads - Kinked	Thickness (Max)	-
· · · · · · · · · · · · · · · · · · ·	Lead Spacing	0.200" (5.08mm)
Report errors?	Lead Style	Formed Leads - Kinked
		Report errors?

#### C325C822F2G5TA Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### C325C822F2G5TA Payment Methods





If you have any question about C325C822F2G5TA, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com