

C326C222F3G5TA

C326C222F3G5TA Information



Part Number	C326C222F3G5TA	
Manufacturer	KEMET	
Category	Capacitors Ceramic Capacitors	
Description	CAP CER 2200PF 25V COG RADIAL	
Package	Radial	
	For the pricing/inventory/lead time, please contact	
us		
	Website: https://www.heisener.com	
	E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



C326C222F3G5TA Specifications

Manufacturer Part Number C326C222F3G5TA Manufacturer KEMET Category Capacitors Caranic Capacitors Caranic Capacitors Package Radial Series Goldmax, 300 Capacitance ±1% Yoltage - Rated ±000 F Yoltage - Rated C0G, NP0 Yoltage - Rated C0G, NP0 Operating Temperature 05% C ~ 125 °C Pactures Low ESX L Applications Bysas, Decoupling Failure Rate - Mounting Type Through Hole Size / Dimension Q000 °L x 0.125 °W (5.08mm x 3.18mm) Size / Dimension 0.300 °C 2.54mm) Height - Seated (Max) 0.000 °L x 0.125 °W (5.08mm x 3.18mm) Lead Spacing 0.100 °C 2.54mm)		
CategoryCapacitorsPackageRadialSeriesGoldmax, 300Capacitance200pFTolerance±1%Voltage - Rated25VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Nounting TypeRadialSize / Dimension0.20° L x 0.125° W (5.08mm x 3.18mm)Fielder Stated.Mounting TypeSolo" (7.62mm)Height - Seated (Max).Joinension.Height - Seated (Max).Lead Spacing.Lead Spacing.Lead StyleFormed Leads - Kinked	Manufacturer Part Number	C326C222F3G5TA
Indext of the section of the sectio	Manufacturer	KEMET
PackageRadialSeriesGoldmax, 300Capacitance2200pFTolerance±1%Voltage - Rated55VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeRadialSize / Dimension0.200° L x 0.125° W (5.08mm x 3.18mm)Fieldy Hamed, Max-Height - Seated (Max)-Height - Seated (Max)-Lead Spacing1.00° (2.54mm)Lead StyleFormed Leads - Kinked	Category	Capacitors
Series Goldmax, 300 Capacitance 2200pF Tolerance ±1% Voltage - Rated 25V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Nounting Type Through Hole Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm) Size / Dimension - Height - Seated (Max) - Thickness (Max) - Lead Spacing 0.100" (2.54mm) Lead Style Formed Leads - Kinked		Ceramic Capacitors
Capacitance2200pFTolerance±1%Voltage - Rated25VTemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HoleSize / Dimension0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.100° (2.54mm)Lead StyleFormed Leads - Kinked	Package	Radial
Tolerance±1%Voltage - Rated25VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)-Lead Spacing0.100° (2.54mm)Lead SpacingFormed Leads - Kinked	Series	Goldmax, 300
Voltage - Rated25VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.100" (2.54mm)Lead StyleFormed Leads - Kinked	Capacitance	2200pF
Temperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.100° (2.54mm)Lead StyleFormed Leads - Kinked	Tolerance	±1%
Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.100" (2.54mm)Lead StyleFormed Leads - Kinked	Voltage - Rated	25V
FeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.100" (2.54mm)Lead StyleFormed Leads - Kinked	Temperature Coefficient	C0G, NP0
Ratings-ApplicationsBypas, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.100" (2.54mm)Lead StyleFormed Leads - Kinked	Operating Temperature	-55°C ~ 125°C
ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.300" (7.62mm)Thickness (Max)-Lead Spacing0.100" (2.54mm)Lead StyleFormed Leads - Kinked	Features	Low ESL
Failure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.300" (7.62mm)Thickness (Max)-Lead Spacing0.100" (2.54mm)Lead StyleFormed Leads - Kinked	Ratings	-
Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.300" (7.62mm)Thickness (Max)-Lead Spacing0.100" (2.54mm)Lead StyleFormed Leads - Kinked	Applications	Bypass, Decoupling
Package / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.300" (7.62mm)Thickness (Max)-Lead Spacing0.100" (2.54mm)Lead StyleFormed Leads - Kinked	Failure Rate	-
Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm) Height - Seated (Max) 0.300" (7.62mm) Thickness (Max) - Lead Spacing 0.100" (2.54mm) Lead Style Formed Leads - Kinked	Mounting Type	Through Hole
Height - Seated (Max)0.300" (7.62mm)Thickness (Max)-Lead Spacing0.100" (2.54mm)Lead StyleFormed Leads - Kinked	Package / Case	Radial
Thickness (Max)-Lead Spacing0.100" (2.54mm)Lead StyleFormed Leads - Kinked	Size / Dimension	0.200" L x 0.125" W (5.08mm x 3.18mm)
Lead Spacing0.100" (2.54mm)Lead StyleFormed Leads - Kinked	Height - Seated (Max)	0.300" (7.62mm)
Lead Style Formed Leads - Kinked	Thickness (Max)	-
	Lead Spacing	0.100" (2.54mm)
Report errors?	Lead Style	Formed Leads - Kinked
		Report errors?

C326C222F3G5TA Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE UARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

C326C222F3G5TA Payment Methods





If you have any question about C326C222F3G5TA, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com