



### C326C301FAG5TA Information

www.heisener.com

For Reference Only

Part Number C326C301FAG5TA

ManufacturerKEMETCategoryCapacitors

Ceramic Capacitors

**Description** CAP CER 300PF 250V C0G RADIAL

Package Radia

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## C326C301FAG5TA Specifications

Manufacturer         C326C301FAG5TA           Manufacturer         KEMET           Category         Capacitors           Package         Radial           Series         Goldmax, 300           Capacitance         300pF           Tolerance         ±1%           Voltage - Rated         250V           Temperature Coefficient         C0G, NPO           Operating Temperature         -55°C ~ 125°C           Features         Low ESL           Ratings         -           Applications         Bypass, Decoupling           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Radial           Size / Dimension         0.200" L x 0.125" W (5.08mm x 3.18mm)           Height - Seated (Max)         0.300" (7.62mm)           Thickness (Max)         -           Lead Spacing         0.100" (2.54mm)           Lead Spacing         Enrmed Leads - Kinked		
Category         Capacitors           Package         Radial           Series         Goldmax, 300           Capacitance         300pF           Tolerance         ±1%           Voltage - Rated         250V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         Low ESL           Ratings         -           Applications         Bypass, Decoupling           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Radial           Size / Dimension         0.200" L x 0.125" W (5.08mm x 3.18mm)           Height - Seated (Max)         0.300" (7.62mm)           Thickness (Max)         -           Lead Spacing         0.100" (2.54mm)	Manufacturer Part Number	C326C301FAG5TA
Package         Radial           Series         Goldmax, 300           Capacitance         300pF           Tolerance         ±1%           Voltage - Rated         250V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         Low ESL           Ratings         -           Applications         Bypass, Decoupling           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Radial           Size / Dimension         0.200" L x 0.125" W (5.08mm x 3.18mm)           Height - Seated (Max)         0.300" (7.62mm)           Thickness (Max)         -           Lead Spacing         0.100" (2.54mm)	Manufacturer	KEMET
Package         Radial           Series         Goldmax, 300           Capacitance         300pF           Tolerance         ±1%           Voltage - Rated         250V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         Low ESL           Ratings         -           Applications         Bypass, Decoupling           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Radial           Size / Dimension         0.200" L x 0.125" W (5.08mm x 3.18mm)           Height - Seated (Max)         0.300" (7.62mm)           Thickness (Max)         -           Lead Spacing         0.100" (2.54mm)	Category	Capacitors
Series         Goldmax, 300           Capacitance         300pF           Tolerance         ±1%           Voltage - Rated         250V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         Low ESL           Ratings         -           Applications         Bypass, Decoupling           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Radial           Size / Dimension         0.200" L x 0.125" W (5.08mm x 3.18mm)           Height - Seated (Max)         0.300" (7.62mm)           Thickness (Max)         -           Lead Spacing         0.100" (2.54mm)		Ceramic Capacitors
Capacitance       300pF         Tolerance       ±1%         Voltage - Rated       250V         Temperature Coefficient       C0G, NP0         Operating Temperature       -55°C ~ 125°C         Features       Low ESL         Ratings       -         Applications       Bypass, Decoupling         Failure Rate       -         Mounting Type       Through Hole         Package / Case       Radial         Size / Dimension       0.200" L x 0.125" W (5.08mm x 3.18mm)         Height - Seated (Max)       0.300" (7.62mm)         Thickness (Max)       -         Lead Spacing       0.100" (2.54mm)	Package	Radial
Tolerance         ±1%           Voltage - Rated         250V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         Low ESL           Ratings         -           Applications         Bypass, Decoupling           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Radial           Size / Dimension         0.200" L x 0.125" W (5.08mm x 3.18mm)           Height - Seated (Max)         0.300" (7.62mm)           Thickness (Max)         -           Lead Spacing         0.100" (2.54mm)	Series	Goldmax, 300
Voltage - Rated250VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.300" (7.62mm)Thickness (Max)-Lead Spacing0.100" (2.54mm)	Capacitance	300pF
Temperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.300" (7.62mm)Thickness (Max)-Lead Spacing0.100" (2.54mm)	Tolerance	±1%
Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.300" (7.62mm)Thickness (Max)-Lead Spacing0.100" (2.54mm)	Voltage - Rated	250V
Features Low ESL  Ratings - Applications Bypass, Decoupling  Failure Rate - Mounting Type Through Hole  Package / Case Radial  Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm)  Height - Seated (Max) 0.300" (7.62mm)  Thickness (Max) - Lead Spacing 0.100" (2.54mm)	Temperature Coefficient	C0G, NP0
Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm) Height - Seated (Max) 0.300" (7.62mm) Thickness (Max) - Lead Spacing 0.100" (2.54mm)	Operating Temperature	-55°C ~ 125°C
Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm) Height - Seated (Max) 0.300" (7.62mm) Thickness (Max) - Lead Spacing 0.100" (2.54mm)	Features	Low ESL
Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm) Height - Seated (Max) 0.300" (7.62mm) Thickness (Max) - Lead Spacing 0.100" (2.54mm)	Ratings	-
Mounting Type Through Hole  Package / Case Radial  Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm)  Height - Seated (Max) 0.300" (7.62mm)  Thickness (Max) -  Lead Spacing 0.100" (2.54mm)	Applications	Bypass, Decoupling
Package / Case Radial Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm) Height - Seated (Max) 0.300" (7.62mm) Thickness (Max) - Lead Spacing 0.100" (2.54mm)	Failure Rate	-
Size / Dimension       0.200" L x 0.125" W (5.08mm x 3.18mm)         Height - Seated (Max)       0.300" (7.62mm)         Thickness (Max)       -         Lead Spacing       0.100" (2.54mm)	Mounting Type	Through Hole
Height - Seated (Max)       0.300" (7.62mm)         Thickness (Max)       -         Lead Spacing       0.100" (2.54mm)	Package / Case	Radial
Thickness (Max)  Lead Spacing  - 0.100" (2.54mm)	Size / Dimension	0.200" L x 0.125" W (5.08mm x 3.18mm)
Lead Spacing 0.100" (2.54mm)	Height - Seated (Max)	0.300" (7.62mm)
	Thickness (Max)	-
Lead Style Formed Leads - Kinked	Lead Spacing	0.100" (2.54mm)
Lead Style 1 Office Leads - Mirked	Lead Style	Formed Leads - Kinked
Report errors?		Report errors?

#### C326C301FAG5TA Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### C326C301FAG5TA Payment Methods




































If you have any question about C326C301FAG5TA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com