

C328C222F3G5TA

C328C222F3G5TA Information

Part



Part Number	C328C222F3G5TA
Manufacturer	KEMET
Category	Capacitors Ceramic Capacitors
Description	CAP CER 2200PF 25V COG RADIAL
Package	Radial
	For the pricing/inventory/lead time, please contact
	us
	Website: https://www.heisener.com
	E-mail: salesdept@heisener.com



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



C328C222F3G5TA Specifications

ManufacturerKEMETCapacitorsCaranic CapacitorsPackageRadialSeriesGoldmax, 300Capacitance200pFTolerance±1%Voltage - Rated25VTomperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.300" (7.62mm)Height - Seated (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked		
CapacitorsPackageRadialPackageGoldmax, 300SeriesGoldmax, 300Capacitance2200pFTolerance±1%Voltage - Rated25VToperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CRatings-ApplicationsBypass, DecouplingFailure Rate-ApplicationsStrough HoleFailure Rate-South SysterStrough HoleFailure Rate0.200° L x 0.125° W (5.08mm x 3.18mm)Height - Seated (Max)0.300° (7.62mm)Thickness (Max)-Lead Spacing6.200° L Striked	Manufacturer Part Number	C328C222F3G5TA
Ceramic CapacitorsPackageRadialSeriesGoldmax, 300Capacitance2200pFTolerance±1%Voltage - Rated25VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Manufacturer	KEMET
PackageRadialSeriesGoldmax, 300Capacitance2200pFTolerance±1%Voltage - Rated25VTomperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HoleSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead SyleFormed Leads - Kinked	Category	Capacitors
Series Goldmax, 300 Capacitance 2200pF Tolerance ±1% Voltage - Rated 25V Temperature Coefficient COG, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing 0.200" (5.08mm) Lead Style Formed Leads - Kinked		Ceramic Capacitors
Capacitance2200pFTolerance±1%Voltage - Rated25VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Package	Radial
Tolerance±1%Voltage - Rated25VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead StyleFormed Leads - Kinked	Series	Goldmax, 300
Voltage - Rated25VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Capacitance	2200pF
Temperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Tolerance	$\pm 1\%$
Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Voltage - Rated	25V
FeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Temperature Coefficient	C0G, NP0
Ratings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing0.200" (5.08mm)Height - Seated (Max)-Dimension-Case of the seated (Max)-Dimension-Dimension-Dimension-Case of the seated (Max)-Dimension	Operating Temperature	-55°C ~ 125°C
ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.300" (7.62mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Features	Low ESL
Failure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.300" (7.62mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Ratings	-
Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.300" (7.62mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Applications	Bypass, Decoupling
Package / CaseRadialSize / Dimension0.200" L x 0.125" W (5.08mm x 3.18mm)Height - Seated (Max)0.300" (7.62mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Failure Rate	-
Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm) Height - Seated (Max) 0.300" (7.62mm) Thickness (Max) - Lead Spacing 0.200" (5.08mm) Lead Style Formed Leads - Kinked	Mounting Type	Through Hole
Height - Seated (Max)0.300" (7.62mm)Thickness (Max)-Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Package / Case	Radial
Thickness (Max) - Lead Spacing 0.200" (5.08mm) Lead Style Formed Leads - Kinked	Size / Dimension	0.200" L x 0.125" W (5.08mm x 3.18mm)
Lead Spacing0.200" (5.08mm)Lead StyleFormed Leads - Kinked	Height - Seated (Max)	0.300" (7.62mm)
Lead Style Formed Leads - Kinked	Thickness (Max)	-
	Lead Spacing	0.200" (5.08mm)
Report errors?	Lead Style	Formed Leads - Kinked
Keport errors:		Report errors?

C328C222F3G5TA Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE UARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

C328C222F3G5TA Payment Methods





If you have any question about C328C222F3G5TA, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com