

C328C562F3G5TA

C328C562F3G5TA Information



Part Number	C328C562F3G5TA
Manufacturer	KEMET
Category	Capacitors Ceramic Capacitors
Description	CAP CER 5600PF 25V COG RADIAL
Package	Radial
	For the pricing/inventory/lead time, please contact
	us
	Website: https://www.heisener.com
	E-mail: salesdept@heisener.com



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



C328C562F3G5TA Specifications

Manufacturer Part NumberC328C562F3G5TAManufacturerKEMETCategoryCapacitorsCategoryCeramic CapacitorsPackageRadialSeriesGoldmax, 300Capacitance5600pFFolerance±1%Voltage - Rated25VPerenting Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-
CategoryCapacitorsCeramic CapacitorsPackageRadialPackageGoldmax, 300Capacitance5600pFFolerance±1%Voltage - Rated25VFomperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Failure Rate-Fa
Ceramic CapacitorsPackageRadialSeriesGoldmax, 300Capacitance5600pFFolerance±1%Voltage - Rated25VTemperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-
PackageRadialBackageGoldmax, 300Capacitance5600pFFolerance±1%Voltage - Rated25VFemperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-
SeriesGoldmax, 300Capacitance5600pFColerance±1%Voltage - Rated25VFemperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFeature Rate-
Capacitance5600pFFolerance±1%Voltage - Rated25VFemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-
Folerance±1%Voltage - Rated25VTemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CSeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-
Voltage - Rated25VCemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-
Femperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-
Deperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-
FeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-
Ratings-ApplicationsBypass, DecouplingFailure Rate-
Applications Bypass, Decoupling Failure Rate -
Failure Rate -
Mounting Type Through Hole
Package / Case Radial
Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm)
Height - Seated (Max)0.300" (7.62mm)
Fhickness (Max) -
Lead Spacing 0.200" (5.08mm)
Lead Style Formed Leads - Kinked
Report errors?

C328C562F3G5TA Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

C328C562F3G5TA Payment Methods





If you have any question about C328C562F3G5TA, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com