

C328C621F3G5TA

C328C621F3G5TA Information



Part Number	C328C621F3G5TA
Manufacturer	KEMET
Category	Capacitors Ceramic Capacitors
Description	CAP CER 620PF 25V COG RADIAL
Package	Radial
	For the pricing/inventory/lead time, please contact
	us
	Website: https://www.heisener.com
	E-mail: salesdept@heisener.com



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



C328C621F3G5TA Specifications

Manufacturer Part Number C328C621F3G5TA Manufacturer KEMET Capacitors Capacitors Caramic Capacitors Ceramic Capacitors Package Radial Series Goldmax, 300 Capacitance 620pF Folerance ±1% Voltage - Rated 25V Comperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling
CategoryCapacitorsCaranic CapacitorsPackageRadialPackageGoldmax, 300Capacitance620pFFolerance±1%Voltage - Rated25VCoperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypas, Decoupling
Ceramic CapacitorsPackageRadialSeriesGoldmax, 300Capacitance620pFFolerance±1%Voltage - Rated25VFemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, Decoupling
PackageRadialSeriesGoldmax, 300Capacitance620pFFolerance±1%Voltage - Rated25VFemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, Decoupling
SeriesGoldmax, 300Capacitance620pFFolerance±1%Voltage - Rated25VFemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, Decoupling
Capacitance620pFFolerance±1%Voltage - Rated25VFemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, Decoupling
Folerance±1%Voltage - Rated25VFemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, Decoupling
Voltage - Rated25VCemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, Decoupling
Femperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, Decoupling
Deperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, Decoupling
FeaturesLow ESLRatings-ApplicationsBypass, Decoupling
Ratings-ApplicationsBypass, Decoupling
Applications Bypass, Decoupling
Zailura Data
Mounting Type Through Hole
Package / Case Radial
Size / Dimension 0.200" L x 0.125" W (5.08mm x 3.18mm)
Height - Seated (Max)0.300" (7.62mm)
Lead Spacing 0.200" (5.08mm)
Lead Style Formed Leads - Kinked
Report errors?

C328C621F3G5TA Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

C328C621F3G5TA Payment Methods





If you have any question about C328C621F3G5TA, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com