



C340C333J1G5TA Information



For Reference Only

Part Number C340C333J1G5TA

Manufacturer KEMET Category Capacitors

Ceramic Capacitors

Description CAP CER 0.033UF 100V NP0 RADIAL

Package Radia

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









C340C333J1G5TA Specifications

Category Capacitors Package Radial Series Goldmax, 300 Capacitance 0.033µF Tolerance ±5% Voltage - Rated 100V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) 0.460" (11.68mm) Thickness (Max) -		
Category Capacitors Package Radial Series Goldmax, 300 Capacitance 0.033µF Tolerance ±5% Voltage - Rated 100V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) 0.460" (11.68mm) Thickness (Max) -	Manufacturer Part Number	C340C333J1G5TA
Package Radial Series Goldmax, 300 Capacitance 0.033μF Tolerance ±5% Voltage - Rated 100V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) 0.460" (11.68mm) Thickness (Max) -	Manufacturer	KEMET
Package Radial Series Goldmax, 300 Capacitance 0.033μF Tolerance ±5% Voltage - Rated 100V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) 0.460" (11.68mm) Thickness (Max) -	Category	Capacitors
Series Goldmax, 300 Capacitance 0.033μF Tolerance ±5% Voltage - Rated 100V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) 0.460" (11.68mm) Thickness (Max) -		Ceramic Capacitors
Capacitance $0.033μF$ Tolerance $\pm 5\%$ Voltage - Rated $100V$ Temperature Coefficient $C0G$, NP0Operating Temperature $-55°C \sim 125°C$ Features-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension $0.400°Lx 0.150°W (10.16mm x 3.81mm)$ Height - Seated (Max) $0.460° (11.68mm)$ Thickness (Max)-	Package	Radial
Tolerance ±5% Voltage - Rated 100V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Ratings Applications General Purpose Failure Rate Mounting Type Through Hole Package / Case Radial Size / Dimension 0.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max)	Series	Goldmax, 300
Voltage - Rated 100V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Ratings Applications General Purpose Failure Rate Mounting Type Through Hole Package / Case Radial Size / Dimension 0.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max)	Capacitance	0.033μF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) Thickness (Max) - COG, NP0 COG, NP0 COG, NP0 Cog Ratings - Cog Ratings - Cog Ratings Co	Tolerance	±5%
Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) Thickness (Max) -	Voltage - Rated	100V
Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) 0.460" (11.68mm) - Thickness (Max) -	Temperature Coefficient	COG, NPO
Ratings - General Purpose Failure Rate - Through Hole Package / Case Radial Size / Dimension 0.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) 0.460" (11.68mm) Thickness (Max) -	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) 0.460" (11.68mm) Thickness (Max) -	Features	-
Failure Rate - Mounting Type Through Hole Package / Case Radial Size / Dimension 0.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) 0.460" (11.68mm) Thickness (Max) -	Ratings	-
Mounting Type Through Hole Package / Case Radial Size / Dimension 0.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) 0.460" (11.68mm) Thickness (Max) -	Applications	General Purpose
Package / Case Radial Size / Dimension 0.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) 0.460" (11.68mm) Thickness (Max) -	Failure Rate	-
Size / Dimension 0.400" L x 0.150" W (10.16mm x 3.81mm) Height - Seated (Max) 0.460" (11.68mm) Thickness (Max) -	Mounting Type	Through Hole
Height - Seated (Max) 7 Thickness (Max) 0.460" (11.68mm) -	Package / Case	Radial
Thickness (Max)	Size / Dimension	0.400" L x 0.150" W (10.16mm x 3.81mm)
	Height - Seated (Max)	0.460" (11.68mm)
Lead Spacing 0.200" (5.08mm)	Thickness (Max)	-
0.200 (3.00mm)	Lead Spacing	0.200" (5.08mm)
Lead Style Straight	Lead Style	Straight
Report errors?		Report errors?

C340C333J1G5TA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

C340C333J1G5TA Payment Methods





















C340C333J1G5TA Shipping Methods













If you have any question about C340C333J1G5TA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com