

C410C129C3G5TA

C410C129C3G5TA Information

Contraction Com	Part Number Manufacturer Category Description Package	C410C129C3G5TA KEMET Capacitors Ceramic Capacitors CAP CER 1.2PF 25V C0G AXIAL Axial For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



C410C129C3G5TA Specifications

ManufacturerKEMETCapacitorsCaramic CapacitorsPackageAxialSeriesAxianx 400Capacitance1.2pFTolerance60.2spFVoltage - Rated25VPorentificient00G, NP0Operating Temperature55°C ~ 125°CPactargs1.2wFRatings-Applications1.2wFFailure Rated-Applications50°C ~ 125°CPactargeSupersophilingFailure Rated-Special Pactard-Applications-Special Pactards-Special Pactards-Special Pactards-Applications-Failure Rate-Special Pactards-Special Pactards-		
CategoryCapacitorsPackageAxialPackageAximax 400Capacitance1.2pFFolerance40.25pFVoltage - Rated25VPorperature CoefficientC0G, NP0Operating Temperature55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsByass, DecouplingFailure Rate-Mounting TypeMinal HolePackage / Case0.095° Di ax 0.170° L (2.41mm x 4.32mm)Height - Seated (Max)-Fickness (Max)-	Manufacturer Part Number	C410C129C3G5TA
ArialPackageAxialSeriesAximax 400Capacitance1.2pFTolerance±0.25pFVoltage - Rated25VPoperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.095" Dia x 0.170" L (2.41mm x 4.32mm)Height - Seated (Max)-Thickness (Max)-	Manufacturer	KEMET
PackageAxialSeriesAximax 400Capacitance1.2pFTolerance±0.2spFVoltage - Rated25VPemperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Package / CaseAxialSize / Dimension0.095" Dia x 0.170" L (2.41mm x 4.32mm)Height - Seated (Max)-Thickness (Max)-	Category	Capacitors
Series Aximax 400 Capacitance 1.2pF Folerance ±0.25pF Voltage - Rated 25V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Deratures Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Size / Dimension 0.095" Dia x 0.170" L (2.41mm x 4.32mm) Height - Seated (Max) - Thickness (Max) -		Ceramic Capacitors
Capacitance1.2pFFolerance=0.25pFVoltage - Rated25VTemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CDeparting TemperatureLow ESLFeatures-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.095" Dia x 0.170" L (2.41mm x 4.32mm)Height - Seated (Max)-Thickness (Max)-	Package	Axial
Folerance±0.25pFVoltage - Rated25VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CDerating TemperatureLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.095" Dia x 0.170" L (2.41mm x 4.32mm)Height - Seated (Max)-Thickness (Max)-	Series	Aximax 400
Voltage - Rated25VPemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.095" Dia x 0.170" L (2.41mm x 4.32mm)Height - Seated (Max)-Thickness (Max)-	Capacitance	1.2pF
Temperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / Case0.095" Dia x 0.170" L (2.41mm x 4.32mm)Size / Dimension-Height - Seated (Max)-Through Mounting Type-Size / Dimension0.095" Dia x 0.170" L (2.41mm x 4.32mm)Height - Seated (Max)-Component-	Tolerance	±0.25pF
Deperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.095" Dia x 0.170" L (2.41mm x 4.32mm)Height - Seated (Max)-Thickness (Max)-	Voltage - Rated	25V
FeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.095" Dia x 0.170" L (2.41mm x 4.32mm)Height - Seated (Max)-Through Case-Konsey (Max)-Case <t< td=""><td>Temperature Coefficient</td><td>C0G, NP0</td></t<>	Temperature Coefficient	C0G, NP0
Ratings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.095" Dia x 0.170" L (2.41mm x 4.32mm)Height - Seated (Max)-Fhickness (Max)-	Operating Temperature	-55°C ~ 125°C
ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.095" Dia x 0.170" L (2.41mm x 4.32mm)Height - Seated (Max)-Thickness (Max)-	Features	Low ESL
Failure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.095" Dia x 0.170" L (2.41mm x 4.32mm)Height - Seated (Max)-Thickness (Max)-	Ratings	-
Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.095" Dia x 0.170" L (2.41mm x 4.32mm)Height - Seated (Max)-Thickness (Max)-	Applications	Bypass, Decoupling
Package / CaseAxialSize / Dimension0.095" Dia x 0.170" L (2.41mm x 4.32mm)Height - Seated (Max)-Thickness (Max)-	Failure Rate	-
Size / Dimension 0.095" Dia x 0.170" L (2.41mm x 4.32mm) Height - Seated (Max) - Thickness (Max) -	Mounting Type	Through Hole
Height - Seated (Max) - Thickness (Max) -	Package / Case	Axial
Thickness (Max) -	Size / Dimension	0.095" Dia x 0.170" L (2.41mm x 4.32mm)
	Height - Seated (Max)	-
ead Spacing	Thickness (Max)	-
	Lead Spacing	-
Lead Style -	Lead Style	-
Report errors?		Report errors?

C410C129C3G5TA Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

C410C129C3G5TA Payment Methods





If you have any question about C410C129C3G5TA, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com