



C410C249C3G5TA Information

Heisener.com

Part Number C410C249C3G5TA

Manufacturer KEMET Category Capacitors

Ceramic Capacitors

Description CAP CER 2.4PF 25V C0G AXIAL

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









C410C249C3G5TA Specifications

Manufacturer Part Number C410C249C3G5TA Manufacturer KEMET Category Capacitors Package Axial Series Aximax 400 Capacitance 2.4pF Tolerance ±0.25pF Voltage - Rated 25V Temperature Coefficient C0G, NP0 Operating Temperature -55°C - 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.095" Dia x 0.170" L (2.41mm x 4.32mm) Height - Seated (Max) - Thickness (Max) -		
Category Capacitors Package Axial Series Aximax 400 Capacitance 2.4pF Tolerance ±0.25pF Voltage - Rated 25V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.095" Dia x 0.170" L (2.41mm x 4.32mm) Height - Seated (Max) - Thickness (Max) -	Manufacturer Part Number	C410C249C3G5TA
Package Axial Series Aximax 400 Capacitance 2.4pF Tolerance ±0.25pF Voltage - Rated 25V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.095" Dia x 0.170" L (2.41mm x 4.32mm) Height - Seated (Max) - Thickness (Max) -	Manufacturer	KEMET
Package Axial Series Aximax 400 Capacitance 2.4pF Tolerance ±0.25pF Voltage - Rated 25V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.095" Dia x 0.170" L (2.41mm x 4.32mm) Height - Seated (Max) - Thickness (Max) -	Category	Capacitors
Series Aximax 400 Capacitance 2.4pF Tolerance ±0.25pF Voltage - Rated 25V Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.095" Dia x 0.170" L (2.41mm x 4.32mm) Height - Seated (Max) - Thickness (Max) -		Ceramic Capacitors
Capacitance 2.4pF Tolerance ±0.25pF Voltage - Rated 25V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.095" Dia x 0.170" L (2.41mm x 4.32mm) Height - Seated (Max) - Thickness (Max) -	Package	Axial
Tolerance ±0.25pF Voltage - Rated 25V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.095" Dia x 0.170" L (2.41mm x 4.32mm) Height - Seated (Max) - Thickness (Max) -	Series	Aximax 400
Voltage - Rated25VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.095" Dia x 0.170" L (2.41mm x 4.32mm)Height - Seated (Max)-Thickness (Max)-	Capacitance	2.4pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.095" Dia x 0.170" L (2.41mm x 4.32mm) Height - Seated (Max) Thickness (Max) -	Tolerance	±0.25pF
Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension O.095" Dia x 0.170" L (2.41mm x 4.32mm) Height - Seated (Max) Thickness (Max) -	Voltage - Rated	25V
Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.095" Dia x 0.170" L (2.41mm x 4.32mm) Height - Seated (Max) - Thickness (Max) -	Temperature Coefficient	COG, NPO
Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.095" Dia x 0.170" L (2.41mm x 4.32mm) Height - Seated (Max) - Thickness (Max) -	Operating Temperature	-55°C ~ 125°C
Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.095" Dia x 0.170" L (2.41mm x 4.32mm) Height - Seated (Max) - Thickness (Max) -	Features	Low ESL
Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.095" Dia x 0.170" L (2.41mm x 4.32mm) Height - Seated (Max) - Thickness (Max) -	Ratings	-
Mounting Type Through Hole Package / Case Axial Size / Dimension 0.095" Dia x 0.170" L (2.41mm x 4.32mm) Height - Seated (Max) - Thickness (Max) -	Applications	Bypass, Decoupling
Package / Case Axial Size / Dimension 0.095" Dia x 0.170" L (2.41mm x 4.32mm) Height - Seated (Max) - Thickness (Max) -	Failure Rate	-
Size / Dimension 0.095" Dia x 0.170" L (2.41mm x 4.32mm) Height - Seated (Max) - Thickness (Max) -	Mounting Type	Through Hole
Height - Seated (Max) - Thickness (Max) -	Package / Case	Axial
Thickness (Max)	Size / Dimension	0.095" Dia x 0.170" L (2.41mm x 4.32mm)
	Height - Seated (Max)	-
1 10 '	Thickness (Max)	-
Lead Spacing -	Lead Spacing	-
Lead Style -	Lead Style	-
Report errors?		Report errors?

C410C249C3G5TA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

C410C249C3G5TA Payment Methods



















C410C249C3G5TA Shipping Methods













If you have any question about C410C249C3G5TA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com