



C420C153J5G5TA Information

Heisener.com

Part Number C420C153J5G5TA

Manufacturer KEMET Category Capacitors

Ceramic Capacitors

Description CAP CER 0.015UF 50V C0G AXIAL

Package Axia

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









C420C153J5G5TA Specifications

| Category Capacitors Package Axial Series Aximax 400 Capacitance 0.015µF Tolerance ±5% Voltage - Rated 50V Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - | | |
|--|--------------------------|---|
| Category Capacitors Package Axial Series Aximax 400 Capacitance 0.015μF Tolerance ±5% Voltage - Rated 50V Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - | Manufacturer Part Number | C420C153J5G5TA |
| Package Axial Series Aximax 400 Capacitance 0.015μF Tolerance ±5% Voltage - Rated 50V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - | Manufacturer | KEMET |
| Package Axial Series Aximax 400 Capacitance 0.015μF Tolerance ±5% Voltage - Rated 50V Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - | Category | Capacitors |
| Series Aximax 400 Capacitance 0.015μF Tolerance ±5% Voltage - Rated 50V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - | | Ceramic Capacitors |
| Capacitance 0.015µF Tolerance ±5% Voltage - Rated 50V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - | Package | Axial |
| Tolerance ±5% Voltage - Rated 50V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm) Height - Seated (Max) - Lead Spacing - Lead Style Lead Style | Series | Aximax 400 |
| Voltage - Rated Temperature Coefficient COG, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm) Height - Seated (Max) Thickness (Max) Lead Spacing - Lead Style | Capacitance | 0.015μF |
| Temperature Coefficient Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - COG, NP0 Avisal COG, NP0 COG, | Tolerance | ±5% |
| Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - Low ESL - Avail - Bypass, Decoupling - Through Hole - 10.100" Dia x 0.200" L (2.54mm x 5.08mm) - Lead Style - - - Lead Style | Voltage - Rated | 50V |
| Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - | Temperature Coefficient | COG, NPO |
| Ratings - Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - Seated Max - Case - C | Operating Temperature | -55°C ~ 125°C |
| Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - | Features | Low ESL |
| Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - | Ratings | - |
| Mounting Type Through Hole Package / Case Axial Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style | Applications | Bypass, Decoupling |
| Package / Case Axial Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - | Failure Rate | - |
| Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - | Mounting Type | Through Hole |
| Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - | Package / Case | Axial |
| Thickness (Max) - Lead Spacing - Lead Style - | Size / Dimension | 0.100" Dia x 0.200" L (2.54mm x 5.08mm) |
| Lead Spacing-Lead Style- | Height - Seated (Max) | - |
| Lead Style - | Thickness (Max) | - |
| | Lead Spacing | - |
| Report errors? | Lead Style | - |
| | | Report errors? |

C420C153J5G5TA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

C420C153J5G5TA Payment Methods





















C420C153J5G5TA Shipping Methods













If you have any question about C420C153J5G5TA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com