

C420C223F3G5TA

C420C223F3G5TA Information

Heisener.com	Part Number Manufacturer Category Description Package	C420C223F3G5TA KEMET Capacitors Ceramic Capacitors CAP CER 0.022UF 25V COG AXIAL Axial For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



C420C223F3G5TA Specifications

ManufacturerKEMETCapacitorsCapacitorsPackageAxialSeriesAxiaa 400Capacitance0.022µFTolerance±1%Voltage - RatedCOG, NPOOperating Temperature CoefficientCOG, NPOOperating Temperature.55°C ~ 125°CRatings-ApplicationsBypas, DecouplingFailure Rate.Mounting TypeShore MailPackage / Case.Siz / Dimension.010° Dia x 0.20° L (2.54mm x 5.08mm)Height - Seated (Max).Tickness (Max).Lead Spacing.Lead Spacing.Lead Spacing.		
CategoryCapacitorsPackageAxialPackageAxiaa 400Capacitance0.022µFCategory±1%Voltage - Rated25VCorperature CoefficientCOG, NP0Operating Temperature.55°C ~ 125°CPattings.25VRatings-ApplicationsBypass, DecouplingFailure Rate.Mounting TypeMinal MolePackage / Case.100° Dia x 0.200° L (2.54mm x 5.08mm)Pickage (Max).Height - Seated (Max).Thickness (Max).Lead Spacing.Lead Spacing.Lead Style.	Manufacturer Part Number	C420C223F3G5TA
Ceramic CapacitorsPackageAxialSeriesAximax 400Capacitance0.022µFTolerance±1%Voltage - Rated25VCogneriting Temperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CPatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / Case0.100" Dia x 0.200" L (2.54mm x 5.08mm)Height - Seated (Max)-Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-Lead Style-	Manufacturer	KEMET
PackageAxialSeriesAximax 400Capacitance0.022µFTolerance1%Voltage - Rated25VComperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeAxialSiz / Dimension0.100° Dia x 0.200° L (2.54mm x 5.08mm)Height - Seated (Max)-Height - Seated (Max)-Height - Seated (Max)-Lead Spacing-Lead Style-Lead Style-Lead Style-Starter <td< td=""><td>Category</td><td>Capacitors</td></td<>	Category	Capacitors
Series Aximax 400 Capacitance 0.022µF Tolerance ±1% Voltage - Rated 25V Tomperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypas, Decoupling Failure Rate - Mounting Type Through Hole Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance0.022µFTolerance±1%Voltage - Rated25VTemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypas, DecouplingFailure Rate-Mounting TypeMinogh HoleSize / Dimension0.100" Dia x 0.200" L (2.54mm x 5.08mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-Starter-Lead Style-Starter<	Package	Axial
Tolerance±1%Voltage - Rated25VTemperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / Case0.100" Dia x 0.200" L (2.54mm x 5.08mm)Height - Seated (Max)-Thickness (Max)-Lead Style-	Series	Aximax 400
Voltage - Rated25VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeHrough HolePackage / CaseAxialSize / Dimension0.100" Dia x 0.200" L (2.54mm x 5.08mm)Height - Seated (Max)-Lead Spacing-Lead Style-Lead Style-	Capacitance	0.022µF
Temperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.100" Dia x 0.200" L (2.54mm x 5.08mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Spacing-Lead Style-State Style-State Style-State Style-State Style-State Style-<	Tolerance	±1%
Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.100" Dia x 0.200" L (2.54mm x 5.08mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing6.Lead Style-Star Lead Style-	Voltage - Rated	25V
FeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.100" Dia x 0.200" L (2.54mm x 5.08mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-Starter-S	Temperature Coefficient	C0G, NP0
Ratings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.100" Dia x 0.200" L (2.54mm x 5.08mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-Height - Seated (Max)-Height - Seated (Max) <td< td=""><td>Operating Temperature</td><td>-55°C ~ 125°C</td></td<>	Operating Temperature	-55°C ~ 125°C
ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.100" Dia x 0.200" L (2.54mm x 5.08mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-Age Style-	Features	Low ESL
Failure Rate-Failure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.100" Dia x 0.200" L (2.54mm x 5.08mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-Height - Seated (Max)-Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-	Ratings	-
Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.100" Dia x 0.200" L (2.54mm x 5.08mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-Annow Style-Height - Seated (Max)-Height - Seated (Max) <td>Applications</td> <td>Bypass, Decoupling</td>	Applications	Bypass, Decoupling
Package / CaseAxialSize / Dimension0.100" Dia x 0.200" L (2.54mm x 5.08mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-Output-Lead Style-	Failure Rate	-
Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Mounting Type	Through Hole
Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-	Package / Case	Axial
Thickness (Max)-Lead Spacing-Lead Style-	Size / Dimension	0.100" Dia x 0.200" L (2.54mm x 5.08mm)
Lead Spacing-Lead Style-	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	-
·	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

C420C223F3G5TA Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE ELARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

C420C223F3G5TA Payment Methods





If you have any question about C420C223F3G5TA, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com