

C420C362JAG5TA

equest a Quote

C420C362JAG5TA Information

Heisener.com	Part Number	C420C362JAG5TA
	Manufacturer	KEMET
	Category	Capacitors Ceramic Capacitors
	Description	CAP CER 3600PF 250V COG AXIAL
	Package	Axial
		For the pricing/inventory/lead time, please contact
For Reference Only		us
		Website: https://www.heisener.com
		E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



C420C362JAG5TA Specifications

Manufacturer Part Number C420C362JAG5TA Manufacturer KEMET Category Capacitors Caranic Capacitors Ceranic Capacitors Package Axial Stries Aximax 400 Capacitance 3600pF Tolerance ±5% Voltage - Rated 250V Operating Temperature 05% ~ 125°C Operating Temperature 55°C ~ 125°C Package 2600 PI Strings - Applications Bypass, Decoupling Faiture Rate - Mounting Type Minoug August Package/Case Axial Stricy Dimension 0.100° Dia x 0.200° L (2.54mm x 5.08mm) Height - Seated (Max) - Height - Seated (Max) - Lead Spacing - Lead Spacing - Lead Spacing - Lead Spacing -		
CategoryCapacitorsPackageAxialPackageAximx 400CapacitanceSofopFCapacitance5%Voltage - Rated250VPorerature CoefficientCoG, NPOOperating Temperature55° C ~ 125°CPactangs.Applications.Applications.Package / Case.Mounting Type.Package / Case.Nounting Type.Pickage / Case.Night - Seated (Max).Height -	Manufacturer Part Number	C420C362JAG5TA
Ceramic CapacitorsPackageAxialSeriesAximax 400Capacitance3600pFTolerance±5%Voltage - Rated250VTemperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HoleSize / Dimension0.100° Dia x 0.200° L (2.54mm x 5.08mm)Height - Seated (Max)-Height - Seated (Max)-Height Seated (Max)-Lead Spacing-Lead Style-	Manufacturer	KEMET
<table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container>	Category	Capacitors
Series Aximax 400 Capacitance 3600pF Tolerance ±5% Voltage - Rated 250V Temperature Coefficient COG, NPO Operating Temperature 55°C ~ 125°C Features Low ESL Ratings - Applications Bypas, Decoupling Mounting Type Hough Hole Size / Dimension Axial Size / Dimension 0.100° Dia x 0.200° L (2.54mm x 5.08mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance3600pFTolerance±5%Voltage - Rated250VTemperature CoefficientC0G, NPOOperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Nounting TypeHolePackage / CaseAxialSize / Dimension-Height - Seated (Max)-Height - Seated (Max)-Lead Spacing-Lead Spacing-Lead Style-Styl	Package	Axial
Tolerance±5%Voltage - Rated250VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / Case0.100" Dia x 0.200" L (2.54mm x 5.08mm)Height - Seated (Max)-Hickness (Max)-Lead Style-Lead Style-	Series	Aximax 400
Voltage - Rated250VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypas, DecouplingFailure Rate-Mounting TypeHolePackage / CaseAxialSize / Dimension0.100" Dia x 0.200" L (2.54mm x 5.08mm)Height - Seated (Max)-Lead Spacing-Lead Style-Style </td <td>Capacitance</td> <td>3600pF</td>	Capacitance	3600pF
Temperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.100" Dia x 0.200" L (2.54mm x 5.08mm)Height - Seated (Max)-Fickness (Max)-Lead Spacing-Lead Spacing-Lead Spacing-State Spacing-<	Tolerance	±5%
Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.100" Dia x 0.200" L (2.54mm x 5.08mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing6.Lead Style-Starter Starter Star	Voltage - Rated	250V
FeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.100" Dia x 0.200" L (2.54mm x 5.08mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-	Temperature Coefficient	C0G, NP0
Ratings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.100" Dia x 0.200" L (2.54mm x 5.08mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-Height - Seated (Max)-Height - Seated (Max) <td< td=""><td>Operating Temperature</td><td>-55°C ~ 125°C</td></td<>	Operating Temperature	-55°C ~ 125°C
ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.100" Dia x 0.200" L (2.54mm x 5.08mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-Height - Seated (Max)-Starter Max-Starter Max </td <td>Features</td> <td>Low ESL</td>	Features	Low ESL
Failure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.100" Dia x 0.200" L (2.54mm x 5.08mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-Height - Seated (Max)-Lead Style-Lead Style- <tr< td=""><td>Ratings</td><td>-</td></tr<>	Ratings	-
Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.100" Dia x 0.200" L (2.54mm x 5.08mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-Height - Seated (Max)-Height - Seate	Applications	Bypass, Decoupling
Package / CaseAxialSize / Dimension0.100" Dia x 0.200" L (2.54mm x 5.08mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-Lead Style-	Failure Rate	-
Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Mounting Type	Through Hole
Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-	Package / Case	Axial
Thickness (Max)-Lead Spacing-Lead Style-	Size / Dimension	0.100" Dia x 0.200" L (2.54mm x 5.08mm)
Lead Spacing-Lead Style-	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	-
·	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

C420C362JAG5TA Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

C420C362JAG5TA Payment Methods





If you have any question about C420C362JAG5TA, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com