



## C420C392JAG5TA Information

Heisener.com

Part Number C420C392JAG5TA

Manufacturer KEMET Category Capacitors

Ceramic Capacitors

**Description** CAP CER 3900PF 250V COG AXIAL

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# C420C392JAG5TA Specifications

Category         Capacitors           Package         Axial           Series         Aximax 400           Capacitance         3900pF           Tolerance         ±5%           Voltage - Rated         250V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         Low ESL           Ratings         -           Applications         Bypass, Decoupling           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Axial           Size / Dimension         0.100" Dia x 0.200" L (2.54mm x 5.08mm)           Height - Seated (Max)         -           Thickness (Max)         -           Lead Spacing         -           Lead Style         -		
Category         Capacitors           Package         Axial           Series         Aximax 400           Capacitance         3900pF           Tolerance         ±5%           Voltage - Rated         250V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         Low ESL           Ratings         -           Applications         Bypass, Decoupling           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Axial           Size / Dimension         0.100" Dia x 0.200" L (2.54mm x 5.08mm)           Height - Seated (Max)         -           Thickness (Max)         -           Lead Spacing         -           Lead Style         -	Manufacturer Part Number	C420C392JAG5TA
Package         Axial           Series         Aximax 400           Capacitance         3900pF           Tolerance         ±5%           Voltage - Rated         250V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         Low ESL           Ratings         -           Applications         Bypass, Decoupling           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Axial           Size / Dimension         0.100" Dia x 0.200" L (2.54mm x 5.08mm)           Height - Seated (Max)         -           Thickness (Max)         -           Lead Spacing         -           Lead Style         -	Manufacturer	KEMET
Package         Axial           Series         Aximax 400           Capacitance         3900pF           Tolerance         ±5%           Voltage - Rated         250V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         Low ESL           Ratings         -           Applications         Bypass, Decoupling           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Axial           Size / Dimension         0.100" Dia x 0.200" L (2.54mm x 5.08mm)           Height - Seated (Max)         -           Thickness (Max)         -           Lead Spacing         -           Lead Style         -	Category	Capacitors
Series         Aximax 400           Capacitance         3900pF           Tolerance         ±5%           Voltage - Rated         250V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         Low ESL           Ratings         -           Applications         Bypass, Decoupling           Failure Rate         -           Mounting Type         Through Hole           Package / Case         Axial           Size / Dimension         0.100" Dia x 0.200" L (2.54mm x 5.08mm)           Height - Seated (Max)         -           Thickness (Max)         -           Lead Spacing         -           Lead Style         -		Ceramic Capacitors
Capacitance       3900pF         Tolerance       ±5%         Voltage - Rated       250V         Temperature Coefficient       C0G, NP0         Operating Temperature       -55°C ~ 125°C         Features       Low ESL         Ratings       -         Applications       Bypass, Decoupling         Failure Rate       -         Mounting Type       Through Hole         Package / Case       Axial         Size / Dimension       0.100" Dia x 0.200" L (2.54mm x 5.08mm)         Height - Seated (Max)       -         Thickness (Max)       -         Lead Spacing       -         Lead Style       -	Package	Axial
Tolerance ±5%  Voltage - Rated 250V  Temperature Coefficient C0G, NP0  Operating Temperature -55°C ~ 125°C  Features Low ESL  Ratings - Applications Bypass, Decoupling  Failure Rate - Mounting Type Through Hole  Package / Case Axial  Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm)  Height - Seated (Max) - Lead Spacing - Lead Style  Lead Style	Series	Aximax 400
Voltage - Rated 250V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Capacitance	3900pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - COG, NP0  COG, NP0  COG, NP0  COG, NP0  COG, NP0  Avisor  - Low ESL  Bypass, Decoupling  - Through Hole - COG, NP0  - Low ESL  Avisor  - COG, NP0  - CO	Tolerance	±5%
Operating Temperature  -55°C ~ 125°C  Features  Low ESL  Ratings  - Applications  Bypass, Decoupling  Failure Rate  - Mounting Type  Through Hole  Package / Case  Axial  Size / Dimension  Height - Seated (Max)  Thickness (Max)  Lead Spacing  Lead Style  -  Low ESL  -  Low ESL  -  Low ESL  -  Now ESL  -  Bypass, Decoupling  -  Low ESL  -  Low ESL  -  Low ESL  -  Bypass, Decoupling  -  Low ESL  -  Bypass, Decoupling  -  Low ESL  -  Low Est  -	Voltage - Rated	250V
Features Low ESL  Ratings - Applications Bypass, Decoupling  Failure Rate - Mounting Type Through Hole  Package / Case Axial  Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm)  Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Temperature Coefficient	COG, NPO
Ratings - Bypass, Decoupling Failure Rate - Through Hole Package / Case Axial Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - Seated (Max) - Case Case Case Case Case Case Case Case	Operating Temperature	-55°C ~ 125°C
Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Features	Low ESL
Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Ratings	-
Mounting Type Through Hole  Package / Case Axial  Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm)  Height - Seated (Max) -  Thickness (Max) -  Lead Spacing -  Lead Style -	Applications	Bypass, Decoupling
Package / Case Axial Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension       0.100" Dia x 0.200" L (2.54mm x 5.08mm)         Height - Seated (Max)       -         Thickness (Max)       -         Lead Spacing       -         Lead Style       -	Mounting Type	Through Hole
Height - Seated (Max)  Thickness (Max)  Lead Spacing  Lead Style  -	Package / Case	Axial
Thickness (Max) - Lead Spacing - Lead Style -	Size / Dimension	0.100" Dia x 0.200" L (2.54mm x 5.08mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	-
·	Lead Spacing	-
Report errors?	Lead Style	-
Report crists:		Report errors?

### C420C392JAG5TA Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## C420C392JAG5TA Payment Methods



















## C420C392JAG5TA Shipping Methods













If you have any question about C420C392JAG5TA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com