



C420C473J2R5TA Information

Heisener.com

Part Number C420C473J2R5TA

Manufacturer KEMET Category Capacitors

Ceramic Capacitors

Description CAP CER 0.047UF 200V X7R AXIAL

Package Axia

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









C420C473J2R5TA Specifications

Manufacturer Part Number C420C473J2R5TA Manufacturer KEMET Category Capacitors Package Axial Series Aximax 400 Capacitance 0.047µF Tolerance ±5% Voltage - Rated 200V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm) Height - Seated (Max) -		
Category Capacitors Package Axial Series Aximax 400 Capacitance 0.047μF Tolerance ±5% Voltage - Rated 200V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm)	Manufacturer Part Number	C420C473J2R5TA
Package Axial Series Aximax 400 Capacitance 0.047μF Tolerance ±5% Voltage - Rated 200V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm)	Manufacturer	KEMET
PackageAxialSeriesAximax 400Capacitance0.047μFTolerance±5%Voltage - Rated200VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.100" Dia x 0.200" L (2.54mm x 5.08mm)	Category	Capacitors
Series Aximax 400 Capacitance 0.047μF Tolerance ±5% Voltage - Rated 200V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm)		Ceramic Capacitors
Capacitance0.047μFTolerance $\pm 5\%$ Voltage - Rated $200V$ Temperature Coefficient $X7R$ Operating Temperature -55° C ~ 125° CFeatures-Ratings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension 0.100° Dia x 0.200° L $(2.54$ mm x 5.08 mm)	Package	Axial
Tolerance ±5% Voltage - Rated 200V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Ratings Applications Bypass, Decoupling Failure Rate Mounting Type Through Hole Package / Case Axial Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm)	Series	Aximax 400
Voltage - Rated200VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.100" Dia x 0.200" L (2.54mm x 5.08mm)	Capacitance	$0.047\mu F$
Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension X7R X7R X7R APR - BYPAS C ~ 125°C - Through Hole Axial 0.100" Dia x 0.200" L (2.54mm x 5.08mm)	Tolerance	±5%
Operating Temperature -55°C ~ 125°C Features - Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm)	Voltage - Rated	200V
Features - Case	Temperature Coefficient	X7R
Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm)	Operating Temperature	-55°C ~ 125°C
Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm)	Features	-
Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm)	Ratings	-
Mounting Type Through Hole Package / Case Axial Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm)	Applications	Bypass, Decoupling
Package / Case Axial Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm)	Failure Rate	-
Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm)	Mounting Type	Through Hole
	Package / Case	Axial
Height - Seated (Max) -	Size / Dimension	0.100" Dia x 0.200" L (2.54mm x 5.08mm)
	Height - Seated (Max)	-
Thickness (Max)	Thickness (Max)	-
Lead Spacing -	Lead Spacing	-
Lead Style -	Lead Style	-
Report errors?		Report errors?

C420C473J2R5TA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

C420C473J2R5TA Payment Methods



















C420C473J2R5TA Shipping Methods













If you have any question about C420C473J2R5TA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com