

C420C511GAG5TA

C420C511GAG5TA Information

Heisener.com

Part Number C420C511GAG5TA

Manufacturer KEMET Category Capacitors

Ceramic Capacitors

Description CAP CER 510PF 250V C0G AXIAL

Package Axia

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









C420C511GAG5TA Specifications

Category Capacitors Package Axial Series Aximax 400 Capacitance 510pF Tolerance ±2% Voltage - Rated 250V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -		
Category Capacitors Package Axial Series Aximax 400 Capacitance 510pF Tolerance ±2% Voltage - Rated 250V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Manufacturer Part Number	C420C511GAG5TA
Package Axial Series Aximax 400 Capacitance 510pF Tolerance ±2% Voltage - Rated 250V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Manufacturer	KEMET
Package Axial Series Aximax 400 Capacitance 510pF Tolerance ±2% Voltage - Rated 250V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Category	Capacitors
Series Aximax 400 Capacitance 510pF Tolerance ±2% Voltage - Rated 250V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 510pF Tolerance ±2% Voltage - Rated 250V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Package	Axial
Tolerance ±2% Voltage - Rated 250V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm) Height - Seated (Max) - Lead Spacing - Lead Style Lead Style	Series	Aximax 400
Voltage - Rated 250V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Capacitance	510pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - COG, NP0 COG, NP0 COG, NP0 COG, NP0 COG, NP0 Avisor - Low ESL Bypass, Decoupling - Through Hole - COG, NP0 - Low ESL Avisor - COG, NP0 - CO	Tolerance	±2%
Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - Low ESL - Low ESL - Low ESL - Now ESL - Bypass, Decoupling - Low ESL - Low ESL - Low ESL - Bypass, Decoupling - Low ESL - Bypass, Decoupling - Low ESL - Low Est -	Voltage - Rated	250V
Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Temperature Coefficient	COG, NPO
Ratings - Bypass, Decoupling Failure Rate - Through Hole Package / Case Axial Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - Seated (Max) - Case Case Case Case Case Case Case Case	Operating Temperature	-55°C ~ 125°C
Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Features	Low ESL
Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Ratings	-
Mounting Type Through Hole Package / Case Axial Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Applications	Bypass, Decoupling
Package / Case Axial Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.100" Dia x 0.200" L (2.54mm x 5.08mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Mounting Type	Through Hole
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style -	Package / Case	Axial
Thickness (Max) - Lead Spacing - Lead Style -	Size / Dimension	0.100" Dia x 0.200" L (2.54mm x 5.08mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	-
·	Lead Spacing	-
Report errors?	Lead Style	-
Report errors.		Report errors?

C420C511GAG5TA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

C420C511GAG5TA Payment Methods



















C420C511GAG5TA Shipping Methods













If you have any question about C420C511GAG5TA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com