



C430C202F2G5TA Information

Heisener.com

Part Number C430C202F2G5TA

Manufacturer KEMET Category Capacitors

Ceramic Capacitors

Description CAP CER 2000PF 200V COG AXIAL

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









C430C202F2G5TA Specifications

Category Capacitors Package Axial Series Aximax 400 Capacitance 2000pF Tolerance ±1% Voltage - Rated 200V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.240" L (3.81mm x 6.10mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing -		
Category Capacitors Package Axial Series Aximax 400 Capacitance 2000pF Tolerance ±1% Voltage - Rated 200V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.240" L (3.81mm x 6.10mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing -	Manufacturer Part Number	C430C202F2G5TA
Package Axial Series Aximax 400 Capacitance 2000pF Tolerance ±1% Voltage - Rated 200V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.240" L (3.81mm x 6.10mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing -	Manufacturer	KEMET
Package Axial Series Aximax 400 Capacitance 2000pF Tolerance ±1% Voltage - Rated 200V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.240" L (3.81mm x 6.10mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing -	Category	Capacitors
Series Aximax 400 Capacitance 2000pF Tolerance ±1% Voltage - Rated 200V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.240" L (3.81mm x 6.10mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing -		Ceramic Capacitors
Capacitance 2000pF Tolerance ±1% Voltage - Rated 200V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.240" L (3.81mm x 6.10mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing -	Package	Axial
Tolerance ±1% Voltage - Rated 200V Temperature Coefficient COG, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.240" L (3.81mm x 6.10mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing -	Series	Aximax 400
Voltage - Rated 200V Temperature Coefficient COG, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.240" L (3.81mm x 6.10mm) Height - Seated (Max) Thickness (Max) - Lead Spacing -	Capacitance	2000pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension O.150" Dia x 0.240" L (3.81mm x 6.10mm) Height - Seated (Max) Thickness (Max) Lead Spacing - COG, NPO -55°C ~ 125°C Low ESL Bypass, Decoupling - Through Hole - Axial - Axial - - Through Hole - - - - - - - - - - - - -	Tolerance	±1%
Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension Height - Seated (Max) - Thickness (Max) Lead Spacing - So ~ 125°C Low ESL Avail Sypass, Decoupling - Through Hole - Comparison 1.50" Dia x 0.240" L (3.81mm x 6.10mm) - Comparison -	Voltage - Rated	200V
Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.240" L (3.81mm x 6.10mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing -	Temperature Coefficient	C0G, NP0
Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.240" L (3.81mm x 6.10mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing -	Operating Temperature	-55°C ~ 125°C
Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.240" L (3.81mm x 6.10mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing -	Features	Low ESL
Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.240" L (3.81mm x 6.10mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing -	Ratings	-
Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.240" L (3.81mm x 6.10mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing -	Applications	Bypass, Decoupling
Package / Case Axial Size / Dimension 0.150" Dia x 0.240" L (3.81mm x 6.10mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing -	Failure Rate	-
Size / Dimension 0.150" Dia x 0.240" L (3.81mm x 6.10mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing -	Mounting Type	Through Hole
Height - Seated (Max) - Thickness (Max) - Lead Spacing -	Package / Case	Axial
Thickness (Max) - Lead Spacing -	Size / Dimension	0.150" Dia x 0.240" L (3.81mm x 6.10mm)
Lead Spacing -	Height - Seated (Max)	-
	Thickness (Max)	-
Lead Style -	Lead Spacing	-
	Lead Style	-
Report errors?		Report errors?

C430C202F2G5TA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

C430C202F2G5TA Payment Methods



















C430C202F2G5TA Shipping Methods













If you have any question about C430C202F2G5TA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com