



C430C362F2G5TA Information

Heisener.com

Part Number C430C362F2G5TA

Manufacturer KEMET Category Capacitors

Ceramic Capacitors

Description CAP CER 3600PF 200V COG AXIAL

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









C430C362F2G5TA Specifications

Manufacturer Part Number C430C362F2G5TA Manufacturer KEMET Category Capacitors Package Axial Series Aximax 400 Capacitance 3600pF Tolerance ±1% Voltage - Rated 200V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.240" L (3.81mm x 6.10mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - Report errors?		
Category Capacitors Package Axial Series Aximax 400 Capacitance 3600pF Tolerance ±1% Voltage - Rated 200V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.240" L (3.81mm x 6.10mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Manufacturer Part Number	C430C362F2G5TA
Package Axial Series Aximax 400 Capacitance 3600pF Tolerance ±1% Voltage - Rated 200V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.240" L (3.81mm x 6.10mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Manufacturer	KEMET
Package Axial Series Aximax 400 Capacitance 3600pF Tolerance ±1% Voltage - Rated 200V Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.240" L (3.81mm x 6.10mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Category	Capacitors
Series Aximax 400 Capacitance 3600pF Tolerance ±1% Voltage - Rated 200V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.240" L (3.81mm x 6.10mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 3600pF Tolerance ±1% Voltage - Rated 200V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.240" L (3.81mm x 6.10mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Package	Axial
Tolerance ±1% Voltage - Rated 200V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.240" L (3.81mm x 6.10mm) Height - Seated (Max) - Lead Spacing - Lead Style - Lead Style	Series	Aximax 400
Voltage - Rated200VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.150" Dia x 0.240" L (3.81mm x 6.10mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-	Capacitance	3600pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - COG, NPO CO	Tolerance	±1%
Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style	Voltage - Rated	200V
Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.240" L (3.81mm x 6.10mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Temperature Coefficient	C0G, NP0
Ratings - Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.240" L (3.81mm x 6.10mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - Case -	Operating Temperature	-55°C ~ 125°C
Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.240" L (3.81mm x 6.10mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Features	Low ESL
Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.240" L (3.81mm x 6.10mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Ratings	-
Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.240" L (3.81mm x 6.10mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style	Applications	Bypass, Decoupling
Package / Case Axial Size / Dimension 0.150" Dia x 0.240" L (3.81mm x 6.10mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.150" Dia x 0.240" L (3.81mm x 6.10mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Mounting Type	Through Hole
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style -	Package / Case	Axial
Thickness (Max) - Lead Spacing - Lead Style -	Size / Dimension	0.150" Dia x 0.240" L (3.81mm x 6.10mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	-
	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

C430C362F2G5TA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

C430C362F2G5TA Payment Methods



















C430C362F2G5TA Shipping Methods













If you have any question about C430C362F2G5TA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com