



C430C822JAG5TA Information

Heisener.com

Part Number C430C822JAG5TA

Manufacturer KEMET Category Capacitors

Ceramic Capacitors

Description CAP CER 8200PF 250V C0G AXIAL

Package Axia

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









C430C822JAG5TA Specifications

Manufacturer Part Number C430C822JAG5TA Manufacturer KEMET Category Capacitors Package Axial Series Aximax 400 Capacitance 8200pF Tolerance ±5% Voltage - Rated 250V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.240" L (3.81mm x 6.10mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing -		
Category Capacitors Package Axial Series Aximax 400 Capacitance 8200pF Tolerance ±5% Voltage - Rated 250V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.240" L (3.81mm x 6.10mm) Height - Seated (Max) - Thickness (Max) -	Manufacturer Part Number	C430C822JAG5TA
Package Axial Series Aximax 400 Capacitance 8200pF Tolerance ±5% Voltage - Rated 250V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.240" L (3.81mm x 6.10mm) Height - Seated (Max) - Thickness (Max) -	Manufacturer	KEMET
Package Axial Series Aximax 400 Capacitance 8200pF Tolerance ±5% Voltage - Rated 250V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.240" L (3.81mm x 6.10mm) Height - Seated (Max) - Thickness (Max) -	Category	Capacitors
Series Aximax 400 Capacitance 8200pF Tolerance ±5% Voltage - Rated 250V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.240" L (3.81mm x 6.10mm) Height - Seated (Max) - Thickness (Max) -		Ceramic Capacitors
Capacitance8200pFTolerance±5%Voltage - Rated250VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.150" Dia x 0.240" L (3.81mm x 6.10mm)Height - Seated (Max)-Thickness (Max)-	Package	Axial
Tolerance ±5% Voltage - Rated 250V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.240" L (3.81mm x 6.10mm) Height - Seated (Max) - Thickness (Max) -	Series	Aximax 400
Voltage - Rated 250V Temperature Coefficient COG, NP0 Operating Temperature -55°C ~ 125°C Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension Height - Seated (Max) Thickness (Max) - 250V COG, NP0 COG, NP0 -55°C ~ 125°C Low ESL Avail - Low ESL At New ESL Avail - Through Hole - Axial - Through Hole - Axial - Through Hole	Capacitance	8200pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.240" L (3.81mm x 6.10mm) Height - Seated (Max) Thickness (Max) -	Tolerance	±5%
Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension O.150" Dia x 0.240" L (3.81mm x 6.10mm) Height - Seated (Max) Thickness (Max) -	Voltage - Rated	250V
Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.240" L (3.81mm x 6.10mm) Height - Seated (Max) - Thickness (Max) -	Temperature Coefficient	C0G, NP0
Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.240" L (3.81mm x 6.10mm) Height - Seated (Max) - Thickness (Max) -	Operating Temperature	-55°C ~ 125°C
Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.240" L (3.81mm x 6.10mm) Height - Seated (Max) - Thickness (Max) -	Features	Low ESL
Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.240" L (3.81mm x 6.10mm) Height - Seated (Max) - Thickness (Max) -	Ratings	-
Mounting Type Through Hole Package / Case Axial Size / Dimension 0.150" Dia x 0.240" L (3.81mm x 6.10mm) Height - Seated (Max) - Thickness (Max) -	Applications	Bypass, Decoupling
Package / Case Axial Size / Dimension 0.150" Dia x 0.240" L (3.81mm x 6.10mm) Height - Seated (Max) - Thickness (Max) -	Failure Rate	-
Size / Dimension 0.150" Dia x 0.240" L (3.81mm x 6.10mm) Height - Seated (Max) - Thickness (Max) -	Mounting Type	Through Hole
Height - Seated (Max) - Thickness (Max) -	Package / Case	Axial
Thickness (Max)	Size / Dimension	0.150" Dia x 0.240" L (3.81mm x 6.10mm)
	Height - Seated (Max)	-
Lead Spacing -	Thickness (Max)	-
	Lead Spacing	-
Lead Style -	Lead Style	-
Report errors?		Report errors?

C430C822JAG5TA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

C430C822JAG5TA Payment Methods



















C430C822JAG5TA Shipping Methods













If you have any question about C430C822JAG5TA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com