



# C7D50DS29D3 Information

www.yelsens.com

For Reference Only

Part Number C7D50DS29D3

Manufacturer TE Connectivity AMP Connectors

Category Connectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

**Description** CONN EDGE DUAL FMALE 100POS .125

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# C7D50DS29D3 Specifications

Manufacturer Part Number         C7D50DS29D3           Manufacturer         TE Connectivity AMP Connectors           Category         Connectors, Interconnects           Package         -           Series         C7 - DS           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         -           Number of Positions         100           Card Thickness         0.054" ~ 0.071" (1.37mm ~ 1.80mm)           Number of Rows         2           Pitch         0.125" (3.18mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Copper Alloy           Contact Finish Thickness         30μin (0.76μm)           Contact Type         -           Color         Black           Flange Feature         Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -           Report errors?	•		
Category       Connectors, Interconnects         Package       -         Series       C7 - DS         Card Type       Non Specified - Dual Edge         Gender       Female         Number of Positions/Bay/Row       -         Number of Positions       100         Card Thickness       0.054" ~ 0.071" (1.37mm ~ 1.80mm)         Number of Rows       2         Pitch       0.125" (3.18mm)         Features       -         Mounting Type       Through Hole         Termination       Solder         Contact Material       Copper Alloy         Contact Finish       Gold         Contact Finish Thickness       30µin (0.76µm)         Contact Type       -         Color       Black         Flange Feature       Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia         Operating Temperature       -	Manufacturer Part Number	C7D50DS29D3	
Package - Series C7 - DS Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row - Number of Positions 100 Card Thickness 0.054" ~ 0.071" (1.37mm ~ 1.80mm) Number of Rows 2 Pitch 0.125" (3.18mm) Features - Mounting Type Through Hole Termination Solder Contact Material Copper Alloy Contact Finish Thickness 30µin (0.76µm) Contact Type - Color Black Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -	Manufacturer	TE Connectivity AMP Connectors	
Package         -           Series         C7 - DS           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         -           Number of Positions         100           Card Thickness         0.054" ~ 0.071" (1.37mm ~ 1.80mm)           Number of Rows         2           Pitch         0.125" (3.18mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Copper Alloy           Contact Finish         Gold           Contact Finish Thickness         30μin (0.76μm)           Contact Type         -           Color         Black           Flange Feature         Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -	Category	Connectors, Interconnects	
Series         C7 - DS           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         -           Number of Positions         100           Card Thickness         0.054" ~ 0.071" (1.37mm ~ 1.80mm)           Number of Rows         2           Pitch         0.125" (3.18mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Copper Alloy           Contact Finish         Gold           Contact Finish Thickness         30μin (0.76μm)           Contact Type         -           Color         Black           Flange Feature         Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -		Card Edge Connectors - Edgeboard Connectors	
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row-Number of Positions100Card Thickness0.054" ~ 0.071" (1.37mm ~ 1.80mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialCopper AlloyContact FinishGoldContact Finish Thickness30µin (0.76µm)Cotoact Type-ColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-	Package	-	
GenderFemaleNumber of Positions/Bay/Row-Number of Positions100Card Thickness0.054" ~ 0.071" (1.37mm ~ 1.80mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialCopper AlloyContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact Type-ColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-	Series	C7 - DS	
Number of Positions/Bay/Row-Number of Positions100Card Thickness0.054" ~ 0.071" (1.37mm ~ 1.80mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialCopper AlloyContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact Type-ColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-	Card Type	Non Specified - Dual Edge	
Number of Positions  Card Thickness  0.054" ~ 0.071" (1.37mm ~ 1.80mm)  Number of Rows  2  Pitch  0.125" (3.18mm)  Features  - Mounting Type  Through Hole  Termination  Solder  Contact Material  Copper Alloy  Contact Finish  Gold  Contact Finish Thickness  30µin (0.76µm)  Contact Type  - Color  Black  Flange Feature  Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature  -	Gender	Female	
Card Thickness0.054" ~ 0.071" (1.37mm ~ 1.80mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialCopper AlloyContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact Type-ColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-	Number of Positions/Bay/Row	-	
Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialCopper AlloyContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact Type-ColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-	Number of Positions	100	
Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialCopper AlloyContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact Type-ColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-	Card Thickness	0.054" ~ 0.071" (1.37mm ~ 1.80mm)	
Features-Mounting TypeThrough HoleTerminationSolderContact MaterialCopper AlloyContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact Type-ColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-	Number of Rows	2	
Mounting TypeThrough HoleTerminationSolderContact MaterialCopper AlloyContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact Type-ColorBlackFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-	Pitch	0.125" (3.18mm)	
Termination  Solder  Contact Material  Copper Alloy  Contact Finish  Gold  Contact Finish Thickness  30μin (0.76μm)  Contact Type  -  Color  Black  Flange Feature  Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature  -	Features	-	
Contact Material Copper Alloy Contact Finish Gold Contact Finish Thickness 30µin (0.76µm)  Contact Type - Color Black Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -	Mounting Type	Through Hole	
Contact Finish  Contact Finish Thickness  30μin (0.76μm)  Contact Type  - Color  Black  Flange Feature  Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature  -	Termination	Solder	
Contact Finish Thickness 30μin (0.76μm)  Contact Type -  Color Black  Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature -	Contact Material	Copper Alloy	
Contact Type - Color Black Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -	Contact Finish	Gold	
Color Black Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -	Contact Finish Thickness	30µin (0.76µm)	
Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -	Contact Type	-	
Operating Temperature -	Color	Black	
	Flange Feature	Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	
Report errors?	Operating Temperature	-	
			Report errors?

#### C7D50DS29D3 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# C7D50DS29D3 Payment Methods



















## C7D50DS29D3 Shipping Methods













If you have any question about C7D50DS29D3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com