



# **C90-3106F12S-3S Information**

Heisener.com

Part Number C90-3106F12S-3S

Manufacturer Harwin Inc.

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PLUG STRGHT 2POS SKT

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# C90-3106F12S-3S Specifications

Manufacturer Part NumberC90-3106F12S-3SManufacturerHarwin Inc.CategoryConnectors, InterconnectsPackage-SeriesC90Connector TypePlug, Female SocketsNumber of Positions2Shell Size - Insert12S-3Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum, Zinc Plated, BlackContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating13AReport errors?		
CategoryConnectors, InterconnectsPackage-SeriesC90Connector TypePlug, Female SocketsNumber of Positions2Shell Size - Insert12S-3Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum, Zinc Plated, BlackContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating13A	Manufacturer Part Number	C90-3106F12S-3S
Circular Connectors  Package - C90 Connector Type Plug, Female Sockets Number of Positions 2 Shell Size - Insert 12S-3 Shell Size, MIL - Connector Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Zinc Plated, Black Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating 1990 Connector Special Connectors Connectors Connector Silver Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating 13A	Manufacturer	Harwin Inc.
Package-SeriesC90Connector TypePlug, Female SocketsNumber of Positions2Shell Size - Insert12S-3Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum, Zinc Plated, BlackContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating13A	Category	Connectors, Interconnects
SeriesC90Connector TypePlug, Female SocketsNumber of Positions2Shell Size - Insert12S-3Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum, Zinc Plated, BlackContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating13A		Circular Connectors
Connector Type Plug, Female Sockets  Number of Positions 2  Shell Size - Insert 12S-3  Shell Size, MIL - Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded  Orientation Keyed  Ingress Protection IP67 - Dust Tight, Waterproof  Shell Material, Finish Aluminum, Zinc Plated, Black  Contact Finish Silver  Features Strain Relief  Voltage - Rated 500VAC, 700VDC  Current Rating 13A	Package	-
Number of Positions2Shell Size - Insert12S-3Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationKeyedIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum, Zinc Plated, BlackContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating13A	Series	C90
Shell Size - Insert  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Solder Cup  Fastening Type  Threaded  Orientation  Keyed  Ingress Protection  IP67 - Dust Tight, Waterproof  Shell Material, Finish  Aluminum, Zinc Plated, Black  Contact Finish  Silver  Features  Strain Relief  Voltage - Rated  500VAC, 700VDC  Current Rating	Connector Type	Plug, Female Sockets
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Zinc Plated, Black Contact Finish Silver Features Strain Relief Voltage - Rated Current Rating  13A	Number of Positions	2
Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded  Orientation Keyed  Ingress Protection IP67 - Dust Tight, Waterproof  Shell Material, Finish Aluminum, Zinc Plated, Black  Contact Finish Silver  Features Strain Relief  Voltage - Rated 500VAC, 700VDC  Current Rating 13A	Shell Size - Insert	12S-3
Termination Solder Cup Fastening Type Threaded Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Zinc Plated, Black Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating 13A	Shell Size, MIL	-
Fastening Type Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Zinc Plated, Black Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating 13A	Mounting Type	Free Hanging (In-Line)
Orientation Keyed Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Zinc Plated, Black Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating 13A	Termination	Solder Cup
Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum, Zinc Plated, Black Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating 13A	Fastening Type	Threaded
Shell Material, Finish  Contact Finish  Silver  Features  Strain Relief  Voltage - Rated  Current Rating  Aluminum, Zinc Plated, Black  Silver  Strain Relief  13A	Orientation	Keyed
Contact Finish Silver  Features Strain Relief  Voltage - Rated 500VAC, 700VDC  Current Rating 13A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features Strain Relief  Voltage - Rated 500VAC, 700VDC  Current Rating 13A	Shell Material, Finish	Aluminum, Zinc Plated, Black
Voltage - Rated 500VAC, 700VDC Current Rating 13A	Contact Finish	Silver
Current Rating 13A	Features	Strain Relief
	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	13A
		Report errors?

#### C90-3106F12S-3S Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### C90-3106F12S-3S Payment Methods



















# C90-3106F12S-3S Shipping Methods













If you have any question about C90-3106F12S-3S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com