



## **CA00COME22-2SB Information**

Heisener.com

Part Number CA00COME22-2SB Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN RCPT 3POS WALL MNT W/SKTS

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **CA00COME22-2SB Specifications**

Manufacturer Part Number       CA00COME22-2SB         Manufacturer       ITT Cannon, LLC         Category       Connectors, Interconnects         Circular Connectors       Circular Connectors         Package       -         Series       MIL-DTL-5015, CA-COM-B         Connector Type       Receptacle, Female Sockets         Number of Positions       3         Shell Size - Insert       22-2         Shell Size, MIL       -         Mounting Type       Panel Mount, Flange         Termination       Solder Cup         Fastening Type       Reverse Bayonet Lock         Orientation       N (Normal)         Ingress Protection       IP67 - Dust Tight, Waterproof         Shell Material, Finish       Aluminum Alloy, Zinc Die Cast, Nickel Plated         Contact Finish       Silver         Features       Strain Relief         Voltage - Rated       900VAC, 1250VDC         Current Rating       74A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-COM-BConnector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - Insert22-2Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated900VAC, 1250VDCCurrent Rating74A	Manufacturer Part Number	CA00COME22-2SB
Circular Connectors  Package - Series MIL-DTL-5015, CA-COM-B Connector Type Receptacle, Female Sockets Number of Positions 3 Shell Size - Insert 22-2 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Features Strain Relief Voltage - Rated 900VAC, 1250VDC Current Rating 74A	Manufacturer	ITT Cannon, LLC
Package - MIL-DTL-5015, CA-COM-B Connector Type Receptacle, Female Sockets Number of Positions 3 Shell Size - Insert 22-2 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 900VAC, 1250VDC Current Rating 74A	Category	Connectors, Interconnects
Series MIL-DTL-5015, CA-COM-B Connector Type Receptacle, Female Sockets Number of Positions 3 Shell Size - Insert 22-2 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 900VAC, 1250VDC Current Rating 74		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - Insert22-2Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated900VAC, 1250VDCCurrent Rating74A	Package	-
Number of Positions  Shell Size - Insert  22-2  Shell Size, MIL  Mounting Type  Panel Mount, Flange  Termination  Solder Cup  Fastening Type  Reverse Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum Alloy, Zinc Die Cast, Nickel Plated  Contact Finish  Features  Strain Relief  Voltage - Rated  900VAC, 1250VDC  Current Rating  74A	Series	MIL-DTL-5015, CA-COM-B
Shell Size - Insert  Shell Size, MIL  Mounting Type  Panel Mount, Flange  Termination  Solder Cup  Fastening Type  Reverse Bayonet Lock  Orientation  N (Normal)  Ingress Protection  IP67 - Dust Tight, Waterproof  Shell Material, Finish  Aluminum Alloy, Zinc Die Cast, Nickel Plated  Contact Finish  Silver  Features  Strain Relief  Voltage - Rated  900VAC, 1250VDC  Current Rating  74A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL  Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 900VAC, 1250VDC Current Rating 74A	Number of Positions	3
Mounting Type Panel Mount, Flange  Termination Solder Cup  Fastening Type Reverse Bayonet Lock  Orientation N (Normal)  Ingress Protection IP67 - Dust Tight, Waterproof  Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated  Contact Finish Silver  Features Strain Relief  Voltage - Rated 900VAC, 1250VDC  Current Rating 74A	Shell Size - Insert	22-2
Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 900VAC, 1250VDC Current Rating 74A	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 900VAC, 1250VDC Current Rating 74A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 900VAC, 1250VDC Current Rating 74A	Termination	Solder Cup
Ingress Protection  Shell Material, Finish  Contact Finish  Features  Strain Relief  Voltage - Rated  Outrent Rating  Potential, Waterproof  Aluminum Alloy, Zinc Die Cast, Nickel Plated  Silver  Strain Relief  74A	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish  Contact Finish  Silver  Features  Strain Relief  Voltage - Rated  900VAC, 1250VDC  Current Rating  74A	Orientation	N (Normal)
Contact Finish Silver  Features Strain Relief Voltage - Rated 900VAC, 1250VDC Current Rating 74A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features Strain Relief  Voltage - Rated 900VAC, 1250VDC  Current Rating 74A	Shell Material, Finish	Aluminum Alloy, Zinc Die Cast, Nickel Plated
Voltage - Rated 900VAC, 1250VDC Current Rating 74A	Contact Finish	Silver
Current Rating 74A	Features	Strain Relief
	Voltage - Rated	900VAC, 1250VDC
Report errors?	Current Rating	74A
		Report errors?

### **CA00COME22-2SB Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **CA00COME22-2SB Payment Methods**





















## **CA00COME22-2SB Shipping Methods**













If you have any question about CA00COME22-2SB, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com