

Heisener.com

CA00COMPG18-6SB01

CA00COMPG18-6SB01 Information

Part Number CA00COMPG18-6SB01

Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 1POS WALL MNT W/SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CA00COMPG18-6SB01 Specifications

Manufacturer Part NumberCA00COMPG18-6SB01ManufacturerITT Cannon, LLCCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-COM-BConnector TypeReceptacle, Female SocketsNumber of Positions1Shell Size - Insert18-6Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeaturesSealing GlandVoltage - Rated900VAC, 1250VDCCurrent RatingIS5A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-COM-BConnector TypeReceptacle, Female SocketsNumber of Positions1Shell Size - Insert18-6Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeaturesSealing GlandVoltage - Rated900VAC, 1250VDCCurrent Rating135A	Manufacturer Part Number	CA00COMPG18-6SB01
Package-SeriesMIL-DTL-5015, CA-COM-BConnector TypeReceptacle, Female SocketsNumber of Positions1Shell Size - Insert18-6Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeaturesSealing GlandVoltage - Rated900VAC, 1250VDCCurrent Rating135A	Manufacturer	ITT Cannon, LLC
Package-SeriesMIL-DTL-5015, CA-COM-BConnector TypeReceptacle, Female SocketsNumber of Positions1Shell Size - Insert18-6Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeaturesSealing GlandVoltage - Rated900VAC, 1250VDCCurrent Rating135A	Category	Connectors, Interconnects
Series MIL-DTL-5015, CA-COM-B Connector Type Receptacle, Female Sockets Number of Positions 1 Shell Size - Insert 18-6 Shell Size, MIL		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions1Shell Size - Insert18-6Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeaturesSealing GlandVoltage - Rated900VAC, 1250VDCCurrent Rating135A	Package	-
Number of Positions1Shell Size - Insert18-6Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeaturesSealing GlandVoltage - Rated900VAC, 1250VDCCurrent Rating135A	Series	MIL-DTL-5015, CA-COM-B
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Sealing Gland Voltage - Rated 900VAC, 1250VDC Current Rating 135A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Features Sealing Gland Voltage - Rated 900VAC, 1250VDC Current Rating 135A	Number of Positions	1
Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Sealing Gland Voltage - Rated 900VAC, 1250VDC Current Rating 135A	Shell Size - Insert	18-6
Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Sealing Gland Voltage - Rated 900VAC, 1250VDC Current Rating 135A	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Sealing Gland Voltage - Rated 900VAC, 1250VDC Current Rating 135A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Sealing Gland Voltage - Rated 900VAC, 1250VDC Current Rating 135A	Termination	Crimp
Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Sealing Gland Voltage - Rated 900VAC, 1250VDC Current Rating 135A	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish Contact Finish Silver Features Sealing Gland Voltage - Rated Ourrent Rating Aluminum Alloy, Zinc Die Cast, Nickel Plated Silver Sealing Gland 135A	Orientation	N (Normal)
Contact Finish Silver Sealing Gland Voltage - Rated 900VAC, 1250VDC Current Rating 135A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features Sealing Gland Voltage - Rated 900VAC, 1250VDC Current Rating 135A	Shell Material, Finish	Aluminum Alloy, Zinc Die Cast, Nickel Plated
Voltage - Rated 900VAC, 1250VDC Current Rating 135A	Contact Finish	Silver
Current Rating 135A	Features	Sealing Gland
	Voltage - Rated	900VAC, 1250VDC
Report errors?	Current Rating	135A
		Report errors?

CA00COMPG18-6SB01 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CA00COMPG18-6SB01 Payment Methods



















CA00COMPG18-6SB01 Shipping Methods













If you have any question about CA00COMPG18-6SB01, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com