

Heisener.com

CA02COME16-10SBF80

CA02COME16-10SBF80 Information

Part Number CA02COME16-10SBF80

Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 3POS BOX MNT W/SKTS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CA02COME16-10SBF80 Specifications

Manufacturer Part NumberCA02COME16-10SBF80ManufacturerITT Cannon, LLCCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-COM-BConnector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - Insert16-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating41A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-COM-BConnector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - Insert16-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDC	Manufacturer Part Number	CA02COME16-10SBF80
Circular Connectors Package Series MIL-DTL-5015, CA-COM-B Connector Type Receptacle, Female Sockets Number of Positions 3 Shell Size - Insert 16-10 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Features - Voltage - Rated Converted Aluminum Alloy Converted Souvac, 700VDC	Manufacturer	ITT Cannon, LLC
Package - MIL-DTL-5015, CA-COM-B Connector Type Receptacle, Female Sockets Number of Positions 3 Shell Size - Insert 16-10 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features - S00VAC, 700VDC	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CA-COM-BConnector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - Insert16-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDC		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - Insert16-10Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDC	Package	-
Number of Positions Shell Size - Insert 16-10 Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Features Voltage - Rated 3 16-10 Aluminum Alloy Lock Panel Mount, Flange Reverse Bayonet Lock N (Normal) Ingress Protection Silver Features - Voltage - Rated	Series	MIL-DTL-5015, CA-COM-B
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Features Voltage - Rated 16-10 Aluminum Alloy Fanel Silver - Voltage - Rated 16-10 Auminum Alloy Fanel Fanel Silver - Voltage - Rated	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC	Number of Positions	3
Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDC	Shell Size - Insert	16-10
Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC	Termination	Crimp
Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish Contact Finish Silver Features - Voltage - Rated Aluminum Alloy, Zinc Die Cast, Nickel Plated Silver - Voltage - Rated	Orientation	N (Normal)
Contact Finish Silver Features - Voltage - Rated Silver - Silver	Ingress Protection	IP67 - Dust Tight, Waterproof
Features - Voltage - Rated 500VAC, 700VDC	Shell Material, Finish	Aluminum Alloy, Zinc Die Cast, Nickel Plated
Voltage - Rated 500VAC, 700VDC	Contact Finish	Silver
	Features	-
Current Rating 41A	Voltage - Rated	500VAC, 700VDC
	Current Rating	41A
Report errors?		Report errors?

CA02COME16-10SBF80 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CA02COME16-10SBF80 Payment Methods



















CA02COME16-10SBF80 Shipping Methods













If you have any question about CA02COME16-10SBF80, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com