

Heisener.com

CA02COME20-16PBF80A176

CA02COME20-16PBF80A176 Information

Part Number CA02COME20-16PBF80A176

Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 9POS BOX MNT W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CA02COME20-16PBF80A176 Specifications

Manufacturer Part NumberCA02COME20-16PBF80A176ManufacturerITT Cannon, LLCCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-COM-BConnector TypeReceptacle, Male PinsNumber of Positions9Shell Size - Insert20-16Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishGoldFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating22A, 41A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-COM-BConnector TypeReceptacle, Male PinsNumber of Positions9Shell Size - Insert20-16Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishGoldFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating22A, 41A	Manufacturer Part Number	CA02COME20-16PBF80A176
Package-SeriesMIL-DTL-5015, CA-COM-BConnector TypeReceptacle, Male PinsNumber of Positions9Shell Size - Insert20-16Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishGoldFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating22A, 41A	Manufacturer	ITT Cannon, LLC
Package-SeriesMIL-DTL-5015, CA-COM-BConnector TypeReceptacle, Male PinsNumber of Positions9Shell Size - Insert20-16Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishGoldFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating22A, 41A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CA-COM-BConnector TypeReceptacle, Male PinsNumber of Positions9Shell Size - Insert20-16Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishGoldFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating22A, 41A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions9Shell Size - Insert20-16Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishGoldFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating22A, 41A	Package	-
Number of Positions Shell Size - Insert 20-16 Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Gold Features Voltage - Rated 500VAC, 700VDC Current Rating 22A, 41A	Series	MIL-DTL-5015, CA-COM-B
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Gold Features - Voltage - Rated 500VAC, 700VDC Current Rating 22A, 41A	Connector Type	Receptacle, Male Pins
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Gold Features - Voltage - Rated 500VAC, 700VDC Current Rating 22A, 41A	Number of Positions	9
Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Gold Features - Voltage - Rated 500VAC, 700VDC Current Rating 22A, 41A	Shell Size - Insert	20-16
Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Gold Features - Voltage - Rated 500VAC, 700VDC Current Rating 22A, 41A	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Gold Features - Voltage - Rated 500VAC, 700VDC Current Rating 22A, 41A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Gold Features - Voltage - Rated 500VAC, 700VDC Current Rating 22A, 41A	Termination	Crimp
Ingress Protection IP67 - Dust Tight, Waterproof Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Gold Features - Voltage - Rated 500VAC, 700VDC Current Rating IP67 - Dust Tight, Waterproof Aluminum Alloy, Zinc Die Cast, Nickel Plated 500VAC, Nickel Plated 22A, 41A	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Voltage - Rated Current Rating Aluminum Alloy, Zinc Die Cast, Nickel Plated Gold 500VAC, 700VDC 22A, 41A	Orientation	N (Normal)
Contact Finish Gold Features - Voltage - Rated 500VAC, 700VDC Current Rating 22A, 41A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features - Voltage - Rated 500VAC, 700VDC Current Rating 22A, 41A	Shell Material, Finish	Aluminum Alloy, Zinc Die Cast, Nickel Plated
Voltage - Rated 500VAC, 700VDC Current Rating 22A, 41A	Contact Finish	Gold
Current Rating 22A, 41A	Features	-
•	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	22A, 41A
		Report errors?

CA02COME20-16PBF80A176 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CA02COME20-16PBF80A176 Payment Methods



















CA02COME20-16PBF80A176 Shipping Methods













If you have any question about CA02COME20-16PBF80A176, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com