



CA02COME22-23PB Information

Heisener.com

Part Number CA02COME22-23PB Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 8POS BOX MNT W/PINS

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CA02COME22-23PB Specifications

Manufacturer Part Number CA02COME22-23PB Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Package - Series MIL-DTL-5015, CA-COM-B Connector Type Receptacle, Male Pins Number of Positions 8 Shell Size - Insert 22-23 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 41A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-COM-BConnector TypeReceptacle, Male PinsNumber of Positions8Shell Size - Insert22-23Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating41A	Manufacturer Part Number	CA02COME22-23PB
Package-SeriesMIL-DTL-5015, CA-COM-BConnector TypeReceptacle, Male PinsNumber of Positions8Shell Size - Insert22-23Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating41A	Manufacturer	ITT Cannon, LLC
Package - MIL-DTL-5015, CA-COM-B Connector Type Receptacle, Male Pins Number of Positions 8 Shell Size - Insert 22-23 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features - Voltage - Rated Current Rating 41A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CA-COM-BConnector TypeReceptacle, Male PinsNumber of Positions8Shell Size - Insert22-23Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating41A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions8Shell Size - Insert22-23Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating41A	Package	-
Number of Positions Shell Size - Insert 22-23 Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Features Voltage - Rated 500VAC, 700VDC Current Rating 41A	Series	MIL-DTL-5015, CA-COM-B
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 41A	Connector Type	Receptacle, Male Pins
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Features - Voltage - Rated 500VAC, 700VDC Current Rating 41A	Number of Positions	8
Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating41A	Shell Size - Insert	22-23
Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 41A	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 41A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 41A	Termination	Solder Cup
Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 41A	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish Contact Finish Silver Features Voltage - Rated Current Rating Aluminum Alloy, Zinc Die Cast, Nickel Plated Silver - Voltage - Rated 500VAC, 700VDC 41A	Orientation	N (Normal)
Contact Finish Silver Features - Voltage - Rated Current Rating 41A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features - Voltage - Rated 500VAC, 700VDC Current Rating 41A	Shell Material, Finish	Aluminum Alloy, Zinc Die Cast, Nickel Plated
Voltage - Rated 500VAC, 700VDC Current Rating 41A	Contact Finish	Silver
Current Rating 41A	Features	-
	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	41A
		Report errors?

CA02COME22-23PB Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CA02COME22-23PB Payment Methods



















CA02COME22-23PB Shipping Methods













If you have any question about CA02COME22-23PB, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com