



### **CA02COME28-22PB Information**

Heisener.com

Part Number CA02COME28-22PB
Manufacturer ITT Cannon, LLC

**Category** Connectors, Interconnects

**Circular Connectors** 

**Description** CONN RCPT 6POS BOX MNT W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **CA02COME28-22PB Specifications**

Manufacturer Part NumberCA02COME28-22PBManufacturerITT Cannon, LLCCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-COM-BConnector TypeReceptacle, Male PinsNumber of Positions6Shell Size - Insert28-22Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating22A, 135AReport errors?		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-COM-BConnector TypeReceptacle, Male PinsNumber of Positions6Shell Size - Insert28-22Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating22A, 135A	Manufacturer Part Number	CA02COME28-22PB
Package-SeriesMIL-DTL-5015, CA-COM-BConnector TypeReceptacle, Male PinsNumber of Positions6Shell Size - Insert28-22Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating22A, 135A	Manufacturer	ITT Cannon, LLC
Package - MIL-DTL-5015, CA-COM-B Connector Type Receptacle, Male Pins Number of Positions 6 Shell Size - Insert 28-22 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating 22A, 135A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CA-COM-BConnector TypeReceptacle, Male PinsNumber of Positions6Shell Size - Insert28-22Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating22A, 135A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions6Shell Size - Insert28-22Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating22A, 135A	Package	-
Number of Positions Shell Size - Insert 28-22 Shell Size, MIL  Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Voltage - Rated 900VAC, 1250VDC Current Rating 22A, 135A	Series	MIL-DTL-5015, CA-COM-B
Shell Size - Insert 28-22  Shell Size, MIL -  Mounting Type Panel Mount, Flange  Termination Solder Cup  Fastening Type Reverse Bayonet Lock  Orientation N (Normal)  Ingress Protection IP67 - Dust Tight, Waterproof  Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated  Contact Finish Silver  Features -  Voltage - Rated 900VAC, 1250VDC  Current Rating 22A, 135A	Connector Type	Receptacle, Male Pins
Shell Size, MIL  Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Features - Voltage - Rated 900VAC, 1250VDC Current Rating 22A, 135A	Number of Positions	6
Mounting Type Panel Mount, Flange  Termination Solder Cup  Fastening Type Reverse Bayonet Lock  Orientation N (Normal)  Ingress Protection IP67 - Dust Tight, Waterproof  Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated  Contact Finish Silver  Features -  Voltage - Rated 900VAC, 1250VDC  Current Rating 22A, 135A	Shell Size - Insert	28-22
Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating 22A, 135A	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating 22A, 135A	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating 22A, 135A	Termination	Solder Cup
Ingress Protection  IP67 - Dust Tight, Waterproof  Aluminum Alloy, Zinc Die Cast, Nickel Plated  Contact Finish  Silver  Features  - Voltage - Rated  900VAC, 1250VDC  Current Rating  22A, 135A	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish  Contact Finish  Silver  Features  Voltage - Rated  Current Rating  Aluminum Alloy, Zinc Die Cast, Nickel Plated  Silver  -  22A, 135A	Orientation	N (Normal)
Contact Finish Silver  Features - Voltage - Rated 900VAC, 1250VDC  Current Rating 22A, 135A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features - Voltage - Rated 900VAC, 1250VDC Current Rating 22A, 135A	Shell Material, Finish	Aluminum Alloy, Zinc Die Cast, Nickel Plated
Voltage - Rated 900VAC, 1250VDC Current Rating 22A, 135A	Contact Finish	Silver
Current Rating 22A, 135A	Features	-
-	Voltage - Rated	900VAC, 1250VDC
Report errors?	Current Rating	22A, 135A
		Report errors?

#### **CA02COME28-22PB Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **CA02COME28-22PB Payment Methods**



















## **CA02COME28-22PB Shipping Methods**













If you have any question about CA02COME28-22PB, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com