



### **CA02COME28-22PB Information**

Heisener.com

Part Number CA02COME28-22PB
Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN RCPT 6POS BOX MNT W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **CA02COME28-22PB Specifications**

| Manufacturer Part NumberCA02COME28-22PBManufacturerITT Cannon, LLCCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-COM-BConnector TypeReceptacle, Male PinsNumber of Positions6Shell Size - Insert28-22Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating22A, 135AReport errors? |                          |  |
|---|--------------------------|--|
| CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-COM-BConnector TypeReceptacle, Male PinsNumber of Positions6Shell Size - Insert28-22Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating22A, 135A   | Manufacturer Part Number | CA02COME28-22PB                              |
| Package-SeriesMIL-DTL-5015, CA-COM-BConnector TypeReceptacle, Male PinsNumber of Positions6Shell Size - Insert28-22Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating22A, 135A  | Manufacturer             | ITT Cannon, LLC                              |
| Package - MIL-DTL-5015, CA-COM-B Connector Type Receptacle, Male Pins Number of Positions 6 Shell Size - Insert 28-22 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating 22A, 135A  | Category                 | Connectors, Interconnects                    |
| SeriesMIL-DTL-5015, CA-COM-BConnector TypeReceptacle, Male PinsNumber of Positions6Shell Size - Insert28-22Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating22A, 135A  |                          | Circular Connectors                          |
| Connector TypeReceptacle, Male PinsNumber of Positions6Shell Size - Insert28-22Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating22A, 135A  | Package                  | -  |
| Number of Positions Shell Size - Insert 28-22 Shell Size, MIL  Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Voltage - Rated 900VAC, 1250VDC Current Rating 22A, 135A   | Series                   | MIL-DTL-5015, CA-COM-B                       |
| Shell Size - Insert 28-22  Shell Size, MIL -  Mounting Type Panel Mount, Flange  Termination Solder Cup  Fastening Type Reverse Bayonet Lock  Orientation N (Normal)  Ingress Protection IP67 - Dust Tight, Waterproof  Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated  Contact Finish Silver  Features -  Voltage - Rated 900VAC, 1250VDC  Current Rating 22A, 135A   | Connector Type           | Receptacle, Male Pins                        |
| Shell Size, MIL  Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Features - Voltage - Rated 900VAC, 1250VDC Current Rating 22A, 135A  | Number of Positions      | 6  |
| Mounting Type Panel Mount, Flange  Termination Solder Cup  Fastening Type Reverse Bayonet Lock  Orientation N (Normal)  Ingress Protection IP67 - Dust Tight, Waterproof  Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated  Contact Finish Silver  Features -  Voltage - Rated 900VAC, 1250VDC  Current Rating 22A, 135A   | Shell Size - Insert      | 28-22  |
| Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating 22A, 135A  | Shell Size, MIL          | -  |
| Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating 22A, 135A   | Mounting Type            | Panel Mount, Flange                          |
| Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating 22A, 135A   | Termination              | Solder Cup                                   |
| Ingress Protection  IP67 - Dust Tight, Waterproof  Aluminum Alloy, Zinc Die Cast, Nickel Plated  Contact Finish  Silver  Features  - Voltage - Rated  900VAC, 1250VDC  Current Rating  22A, 135A  | Fastening Type           | Reverse Bayonet Lock                         |
| Shell Material, Finish  Contact Finish  Silver  Features  Voltage - Rated  Current Rating  Aluminum Alloy, Zinc Die Cast, Nickel Plated  Silver  -  22A, 135A   | Orientation              | N (Normal)                                   |
| Contact Finish Silver  Features - Voltage - Rated 900VAC, 1250VDC  Current Rating 22A, 135A   | Ingress Protection       | IP67 - Dust Tight, Waterproof                |
| Features - Voltage - Rated 900VAC, 1250VDC Current Rating 22A, 135A   | Shell Material, Finish   | Aluminum Alloy, Zinc Die Cast, Nickel Plated |
| Voltage - Rated 900VAC, 1250VDC Current Rating 22A, 135A  | Contact Finish           | Silver                                       |
| Current Rating 22A, 135A  | Features                 | -  |
| -   | Voltage - Rated          | 900VAC, 1250VDC                              |
| Report errors?  | Current Rating           | 22A, 135A                                    |
|   |                          | Report errors?                               |

#### **CA02COME28-22PB Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **CA02COME28-22PB Payment Methods**



















## **CA02COME28-22PB Shipping Methods**













If you have any question about CA02COME28-22PB, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com