

Heisener.com

CA02COML14S-6PA206

CA02COML14S-6PA206 Information

Part Number CA02COML14S-6PA206

Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 6POS BOX MNT W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CA02COML14S-6PA206 Specifications

Manufacturer Part Number CA02COML14S-6PA206 Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Package - Series MIL-DTL-5015, CA-COM Connector Type Receptacle, Male Pins Number of Positions 6 Shell Size - Insert 14S-6 Shell Size, MIL - Mounting Type Panel Mount, Flange; Through Hole Termination Solder Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Plated, Black Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating 22A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-COMConnector TypeReceptacle, Male PinsNumber of Positions6Shell Size - Insert14S-6Shell Size, MIL-Mounting TypePanel Mount, Flange; Through HoleTerminationSolderFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Zinc Plated, BlackContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating22A	Manufacturer Part Number	CA02COML14S-6PA206
Circular Connectors Package - Series MIL-DTL-5015, CA-COM Connector Type Receptacle, Male Pins Number of Positions 6 Shell Size - Insert 14S-6 Shell Size, MIL - Mounting Type Panel Mount, Flange; Through Hole Termination Solder Fastening Type Threaded Orientation N (Normal) Ingress Protection N (Normal) Ingress Protection Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating	Manufacturer	ITT Cannon, LLC
Package - Series MIL-DTL-5015, CA-COM Connector Type Receptacle, Male Pins Number of Positions 6 Shell Size - Insert 14S-6 Shell Size, MIL - Mounting Type Panel Mount, Flange; Through Hole Termination Solder Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Plated, Black Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating 22A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CA-COMConnector TypeReceptacle, Male PinsNumber of Positions6Shell Size - Insert14S-6Shell Size, MIL-Mounting TypePanel Mount, Flange; Through HoleTerminationSolderFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Zinc Plated, BlackContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating22A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions6Shell Size - Insert14S-6Shell Size, MIL-Mounting TypePanel Mount, Flange; Through HoleTerminationSolderFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Zinc Plated, BlackContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating22A	Package	-
Number of Positions Shell Size - Insert 14S-6 Shell Size, MIL Mounting Type Panel Mount, Flange; Through Hole Termination Solder Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Plated, Black Contact Finish Features - Voltage - Rated 200VAC, 250VDC Current Rating 22A	Series	MIL-DTL-5015, CA-COM
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Flange; Through Hole Termination Solder Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Plated, Black Contact Finish Features - Voltage - Rated 200VAC, 250VDC Current Rating 14S-6 Panel Alwounting Alwounting 14S-6 14	Connector Type	Receptacle, Male Pins
Shell Size, MIL Mounting Type Panel Mount, Flange; Through Hole Termination Solder Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Plated, Black Contact Finish Features - Voltage - Rated 200VAC, 250VDC Current Rating 22A	Number of Positions	6
Mounting Type Panel Mount, Flange; Through Hole Termination Solder Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Plated, Black Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating 22A	Shell Size - Insert	14S-6
Termination Solder Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Plated, Black Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating 22A	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Plated, Black Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating Threaded 22A	Mounting Type	Panel Mount, Flange; Through Hole
Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Plated, Black Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating 22A	Termination	Solder
Ingress Protection IP65 - Dust Tight, Water Resistant Aluminum Alloy, Zinc Plated, Black Contact Finish Silver Features Voltage - Rated 200VAC, 250VDC Current Rating 22A	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Features - Voltage - Rated Current Rating Aluminum Alloy, Zinc Plated, Black Silver - 200VAC, 250VDC 22A	Orientation	N (Normal)
Contact Finish Silver Features - Voltage - Rated Current Rating 200VAC, 250VDC 22A	Ingress Protection	IP65 - Dust Tight, Water Resistant
Features - Voltage - Rated 200VAC, 250VDC Current Rating 22A	Shell Material, Finish	Aluminum Alloy, Zinc Plated, Black
Voltage - Rated 200VAC, 250VDC Current Rating 22A	Contact Finish	Silver
Current Rating 22A	Features	-
	Voltage - Rated	200VAC, 250VDC
Report errors?	Current Rating	22A
		Report errors?

CA02COML14S-6PA206 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CA02COML14S-6PA206 Payment Methods



















CA02COML14S-6PA206 Shipping Methods













If you have any question about CA02COML14S-6PA206, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com