



## **CA02COML20-27P Information**

Heisener.com

Part Number CA02COML20-27P Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN RCPT 14POS BOX MNT W/PINS

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **CA02COML20-27P Specifications**

Manufacturer Part Number       CA02COML20-27P         Manufacturer       ITT Cannon, LLC         Category       Connectors, Interconnects         Package       -         Series       MIL-DTL-5015, CA-COM         Connector Type       Receptacle, Male Pins         Number of Positions       14         Shell Size - Insert       20-27         Shell Size, MIL       -         Mounting Type       Panel Mount, Flange; Through Hole         Termination       Solder         Fastening Type       Threaded         Orientation       N (Normal)         Ingress Protection       IP65 - Dust Tight, Water Resistant         Shell Material, Finish       Aluminum Alloy, Zinc Die Cast, Nickel Plated         Contact Finish       Silver         Features       -         Voltage - Rated       500VAC, 700VDC         Current Rating       22A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-COMConnector TypeReceptacle, Male PinsNumber of Positions14Shell Size - Insert20-27Shell Size, MIL-Mounting TypePanel Mount, Flange; Through HoleTerminationSolderFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating22A	Manufacturer Part Number	CA02COML20-27P
Package-SeriesMIL-DTL-5015, CA-COMConnector TypeReceptacle, Male PinsNumber of Positions14Shell Size - Insert20-27Shell Size, MIL-Mounting TypePanel Mount, Flange; Through HoleTerminationSolderFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating22A	Manufacturer	ITT Cannon, LLC
Package-SeriesMIL-DTL-5015, CA-COMConnector TypeReceptacle, Male PinsNumber of Positions14Shell Size - Insert20-27Shell Size, MIL-Mounting TypePanel Mount, Flange; Through HoleTerminationSolderFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating22A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CA-COMConnector TypeReceptacle, Male PinsNumber of Positions14Shell Size - Insert20-27Shell Size, MIL-Mounting TypePanel Mount, Flange; Through HoleTerminationSolderFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating22A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions14Shell Size - Insert20-27Shell Size, MIL-Mounting TypePanel Mount, Flange; Through HoleTerminationSolderFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating22A	Package	-
Number of Positions  Shell Size - Insert  20-27  Shell Size, MIL  Mounting Type  Panel Mount, Flange; Through Hole  Termination  Solder  Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  IP65 - Dust Tight, Water Resistant  Shell Material, Finish  Aluminum Alloy, Zinc Die Cast, Nickel Plated  Contact Finish  Features  Voltage - Rated  500VAC, 700VDC  Current Rating  14  20-27  Panel Mount, Flange; Through Hole  N (Normal)  Logical Flange; Through Hole  Solder  Fanel Mount, Flange; Through Hole  Colder  Fanel Mount, Flange; Through Hole  Solder  Fateres  10  11  12  13  14  14  14  14  15  16  16  16  17  17  17  18  18  18  18  18  18  18	Series	MIL-DTL-5015, CA-COM
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Flange; Through Hole Termination Solder Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 22A	Connector Type	Receptacle, Male Pins
Shell Size, MIL  Mounting Type Panel Mount, Flange; Through Hole  Termination Solder Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Features - Voltage - Rated 500VAC, 700VDC Current Rating 22A	Number of Positions	14
Mounting Type Panel Mount, Flange; Through Hole  Termination Solder  Fastening Type Threaded  Orientation N (Normal)  Ingress Protection IP65 - Dust Tight, Water Resistant  Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated  Contact Finish Silver  Features -  Voltage - Rated 500VAC, 700VDC  Current Rating 22A	Shell Size - Insert	20-27
Termination Solder Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 22A	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 22A	Mounting Type	Panel Mount, Flange; Through Hole
Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating 22A	Termination	Solder
Ingress Protection  IP65 - Dust Tight, Water Resistant  Aluminum Alloy, Zinc Die Cast, Nickel Plated  Contact Finish  Silver  Features  - Voltage - Rated  500VAC, 700VDC  Current Rating	Fastening Type	Threaded
Shell Material, Finish  Contact Finish  Silver  Features  Voltage - Rated  Current Rating  Aluminum Alloy, Zinc Die Cast, Nickel Plated  Silver  -  22A	Orientation	N (Normal)
Contact Finish Silver  Features - Voltage - Rated Current Rating 22A	Ingress Protection	IP65 - Dust Tight, Water Resistant
Features - Voltage - Rated 500VAC, 700VDC Current Rating 22A	Shell Material, Finish	Aluminum Alloy, Zinc Die Cast, Nickel Plated
Voltage - Rated 500VAC, 700VDC Current Rating 22A	Contact Finish	Silver
Current Rating 22A	Features	-
	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	22A
		Report errors?

### **CA02COML20-27P Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **CA02COML20-27P Payment Methods**



















# **CA02COML20-27P Shipping Methods**













If you have any question about CA02COML20-27P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com