

Heisener.com

## CA06COME14S-5SDN

## **CA06COME14S-5SDN Information**

Part Number CA06COME14S-5SDN
Manufacturer ITT Cannon, LLC

**Category** Connectors, Interconnects

Circular Connectors

**Description** CONN PLUG 5POS INLINE W/SKTS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **CA06COME14S-5SDN Specifications**

Manufacturer Part Number       CA06COME14S-5SDN         Manufacturer       ITT Cannon, LLC         Category       Connectors, Interconnects         Package       -         Series       MIL-DTL-5015, CA-COM         Connector Type       Plug, Female Sockets         Number of Positions       5         Shell Size - Insert       14S-5         Shell Size, MIL       -         Mounting Type       Free Hanging (In-Line)         Termination       Solder Cup         Fastening Type       Threaded         Orientation       N (Normal)         Ingress Protection       IP67 - Dust Tight, Waterproof         Shell Material, Finish       Aluminum Alloy, Zinc Die Cast, Nickel Plated         Contact Finish       Silver         Features       Shrink Boot Adapter         Voltage - Rated       200VAC, 250VDC         Current Rating       22A     Report errors?		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-COMConnector TypePlug, Female SocketsNumber of Positions5Shell Size - Insert14S-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeaturesShrink Boot AdapterVoltage - Rated200VAC, 250VDCCurrent Rating22A	Manufacturer Part Number	CA06COME14S-5SDN
Circular Connectors  Package - Series MIL-DTL-5015, CA-COM Connector Type Plug, Female Sockets Number of Positions 5 Shell Size - Insert 14S-5 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Features Shrink Boot Adapter Voltage - Rated Current Rating 22A	Manufacturer	ITT Cannon, LLC
Package - MIL-DTL-5015, CA-COM Connector Type Plug, Female Sockets Number of Positions 5 Shell Size - Insert 14S-5 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Shrink Boot Adapter Voltage - Rated 200VAC, 250VDC Current Rating 22A	Category	Connectors, Interconnects
Series MIL-DTL-5015, CA-COM Connector Type Plug, Female Sockets Number of Positions 5 Shell Size - Insert 14S-5 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Shrink Boot Adapter Voltage - Rated 200VAC, 250VDC Current Rating 22A		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions5Shell Size - Insert14S-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeaturesShrink Boot AdapterVoltage - Rated200VAC, 250VDCCurrent Rating22A	Package	-
Number of Positions5Shell Size - Insert14S-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeaturesShrink Boot AdapterVoltage - Rated200VAC, 250VDCCurrent Rating22A	Series	MIL-DTL-5015, CA-COM
Shell Size - Insert  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Solder Cup  Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  IP67 - Dust Tight, Waterproof  Shell Material, Finish  Aluminum Alloy, Zinc Die Cast, Nickel Plated  Contact Finish  Silver  Features  Shrink Boot Adapter  Voltage - Rated  200VAC, 250VDC  Current Rating  22A	Connector Type	Plug, Female Sockets
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Shrink Boot Adapter  Voltage - Rated 200VAC, 250VDC Current Rating 22A	Number of Positions	5
Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded  Orientation N (Normal)  Ingress Protection IP67 - Dust Tight, Waterproof  Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated  Contact Finish Silver  Features Shrink Boot Adapter  Voltage - Rated 200VAC, 250VDC  Current Rating 22A	Shell Size - Insert	14S-5
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Shrink Boot Adapter Voltage - Rated 200VAC, 250VDC Current Rating 22A	Shell Size, MIL	-
Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum Alloy, Zinc Die Cast, Nickel Plated  Contact Finish  Silver  Features  Shrink Boot Adapter  Voltage - Rated  200VAC, 250VDC  Current Rating	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Shrink Boot Adapter Voltage - Rated 200VAC, 250VDC Current Rating 22A	Termination	Solder Cup
Ingress Protection  IP67 - Dust Tight, Waterproof  Aluminum Alloy, Zinc Die Cast, Nickel Plated  Contact Finish  Silver  Features  Shrink Boot Adapter  Voltage - Rated  200VAC, 250VDC  Current Rating	Fastening Type	Threaded
Shell Material, Finish  Contact Finish  Silver  Features  Shrink Boot Adapter  Voltage - Rated  Current Rating  Aluminum Alloy, Zinc Die Cast, Nickel Plated  Silver  Shrink Boot Adapter  200VAC, 250VDC	Orientation	N (Normal)
Contact Finish Silver Shrink Boot Adapter Voltage - Rated Current Rating 200VAC, 250VDC 22A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features Shrink Boot Adapter  Voltage - Rated 200VAC, 250VDC  Current Rating 22A	Shell Material, Finish	Aluminum Alloy, Zinc Die Cast, Nickel Plated
Voltage - Rated 200VAC, 250VDC Current Rating 22A	Contact Finish	Silver
Current Rating 22A	Features	Shrink Boot Adapter
-	Voltage - Rated	200VAC, 250VDC
Report errors?	Current Rating	22A
		Report errors?

#### **CA06COME14S-5SDN Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **CA06COME14S-5SDN Payment Methods**



















## **CA06COME14S-5SDN Shipping Methods**













If you have any question about CA06COME14S-5SDN, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com