

Heisener.com

# CA06COME14S-7SBF80

#### CA06COME14S-7SBF80 Information

Part Number CA06COME14S-7SBF80

Manufacturer ITT Cannon, LLC

**Category** Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PLUG 3POS INLINE W/SKTS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# CA06COME14S-7SBF80 Specifications

Manufacturer Part NumberCA06COME14S-7SBF80ManufacturerITT Cannon, LLCCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-COM-BConnector TypePlug, Female SocketsNumber of Positions3Shell Size - Insert14S-7Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent RatingEeport errors?		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-COM-BConnector TypePlug, Female SocketsNumber of Positions3Shell Size - Insert14S-7Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating22A	Manufacturer Part Number	CA06COME14S-7SBF80
Package-SeriesMIL-DTL-5015, CA-COM-BConnector TypePlug, Female SocketsNumber of Positions3Shell Size - Insert14S-7Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating22A	Manufacturer	ITT Cannon, LLC
Package-SeriesMIL-DTL-5015, CA-COM-BConnector TypePlug, Female SocketsNumber of Positions3Shell Size - Insert14S-7Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating22A	Category	Connectors, Interconnects
Series MIL-DTL-5015, CA-COM-B  Connector Type Plug, Female Sockets  Number of Positions 3  Shell Size - Insert 14S-7  Shell Size, MIL -  Mounting Type Free Hanging (In-Line)  Termination Crimp  Fastening Type Reverse Bayonet Lock  Orientation N (Normal)  Ingress Protection Pf67 - Dust Tight, Waterproof  Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated  Contact Finish Silver  Features Strain Relief  Voltage - Rated 500VAC, 700VDC  Current Rating 23		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions3Shell Size - Insert14S-7Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating22A	Package	-
Number of Positions3Shell Size - Insert14S-7Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating22A	Series	MIL-DTL-5015, CA-COM-B
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line)  Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating 22A	Connector Type	Plug, Female Sockets
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal)  Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated  Contact Finish Features Strain Relief  Voltage - Rated 500VAC, 700VDC  Current Rating 22A	Number of Positions	3
Mounting Type Free Hanging (In-Line)  Termination Crimp  Fastening Type Reverse Bayonet Lock  Orientation N (Normal)  Ingress Protection IP67 - Dust Tight, Waterproof  Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated  Contact Finish Silver  Features Strain Relief  Voltage - Rated 500VAC, 700VDC  Current Rating 22A	Shell Size - Insert	14S-7
Termination Crimp Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating 22A	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating 22A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating 22A	Termination	Crimp
Ingress Protection  IP67 - Dust Tight, Waterproof  Aluminum Alloy, Zinc Die Cast, Nickel Plated  Contact Finish  Silver  Features  Strain Relief  Voltage - Rated  500VAC, 700VDC  Current Rating	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish  Contact Finish  Silver  Features  Strain Relief  Voltage - Rated  Current Rating  Aluminum Alloy, Zinc Die Cast, Nickel Plated  Silver  Strain Relief  22A	Orientation	N (Normal)
Contact Finish Silver Strain Relief Voltage - Rated Current Rating Silver Strain Relief 22A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features Strain Relief  Voltage - Rated 500VAC, 700VDC  Current Rating 22A	Shell Material, Finish	Aluminum Alloy, Zinc Die Cast, Nickel Plated
Voltage - Rated 500VAC, 700VDC Current Rating 22A	Contact Finish	Silver
Current Rating 22A	Features	Strain Relief
	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	22A
		Report errors?

#### CA06COME14S-7SBF80 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

#### CA06COME14S-7SBF80 Payment Methods



















## **CA06COME14S-7SBF80 Shipping Methods**













If you have any question about CA06COME14S-7SBF80, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com