

# CA06COME16-11SB

### **CA06COME16-11SB Information**

Heisener.com

Part Number CA06COME16-11SB Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PLUG 2POS INLINE W/SKTS

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **CA06COME16-11SB Specifications**

Manufacturer Part Number       CA06COME16-11SB         Manufacturer       ITT Cannon, LLC         Category       Connectors, Interconnects         Circular Connectors         Package       -         Series       MIL-DTL-5015, CA-COM-B         Connector Type       Plug, Female Sockets         Number of Positions       2         Shell Size - Insert       16-11         Shell Size, MIL       -         Mounting Type       Free Hanging (In-Line)         Termination       Solder Cup         Fastening Type       Reverse Bayonet Lock         Orientation       N (Normal)         Ingress Protection       IP67 - Dust Tight, Waterproof         Shell Material, Finish       Aluminum Alloy, Zinc Die Cast, Nickel Plated         Contact Finish       Silver         Features       Strain Relief         Voltage - Rated       500VAC, 700VDC         Current Rating       41A		
Category Connectors, Interconnects Circular Connectors  Package - Series MIL-DTL-5015, CA-COM-B Connector Type Plug, Female Sockets Number of Positions 2 Shell Size - Insert I6-11 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated Current Rating 41A	Manufacturer Part Number	CA06COME16-11SB
Circular Connectors  Package - Series MIL-DTL-5015, CA-COM-B Connector Type Plug, Female Sockets Number of Positions 2 Shell Size - Insert 16-11 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating  41A	Manufacturer	ITT Cannon, LLC
Package - MIL-DTL-5015, CA-COM-B Connector Type Plug, Female Sockets Number of Positions 2 Shell Size - Insert 16-11 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating 41A	Category	Connectors, Interconnects
Series MIL-DTL-5015, CA-COM-B  Connector Type Plug, Female Sockets  Number of Positions 2  Shell Size - Insert 16-11  Shell Size, MIL -  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Reverse Bayonet Lock  Orientation N (Normal)  Ingress Protection IP67 - Dust Tight, Waterproof  Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated  Contact Finish Silver  Features Strain Relief  Voltage - Rated 500VAC, 700VDC  Current Rating 41A		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions2Shell Size - Insert16-11Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating41A	Package	-
Number of Positions  Shell Size - Insert  16-11  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Solder Cup  Fastening Type  Reverse Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum Alloy, Zinc Die Cast, Nickel Plated  Contact Finish  Features  Strain Relief  Voltage - Rated  500VAC, 700VDC  Current Rating  41A	Series	MIL-DTL-5015, CA-COM-B
Shell Size - Insert  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Solder Cup  Fastening Type  Reverse Bayonet Lock  Orientation  N (Normal)  Ingress Protection  IP67 - Dust Tight, Waterproof  Shell Material, Finish  Aluminum Alloy, Zinc Die Cast, Nickel Plated  Contact Finish  Silver  Features  Strain Relief  Voltage - Rated  500VAC, 700VDC  Current Rating  41A	Connector Type	Plug, Female Sockets
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Reverse Bayonet Lock Orientation N (Normal)  Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated  Contact Finish Silver Features Strain Relief  Voltage - Rated 500VAC, 700VDC  Current Rating 41A	Number of Positions	2
Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Reverse Bayonet Lock  Orientation N (Normal)  Ingress Protection IP67 - Dust Tight, Waterproof  Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated  Contact Finish Silver  Features Strain Relief  Voltage - Rated 500VAC, 700VDC  Current Rating 41A	Shell Size - Insert	16-11
Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating 41A	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating 41A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating 41A	Termination	Solder Cup
Ingress Protection  IP67 - Dust Tight, Waterproof  Shell Material, Finish  Aluminum Alloy, Zinc Die Cast, Nickel Plated  Contact Finish  Silver  Features  Strain Relief  Voltage - Rated  500VAC, 700VDC  Current Rating  41A	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish  Contact Finish  Silver  Features  Strain Relief  Voltage - Rated  Current Rating  Aluminum Alloy, Zinc Die Cast, Nickel Plated  Silver  Strain Relief  41A	Orientation	N (Normal)
Contact Finish Silver  Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating 41A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features Strain Relief  Voltage - Rated 500VAC, 700VDC  Current Rating 41A	Shell Material, Finish	Aluminum Alloy, Zinc Die Cast, Nickel Plated
Voltage - Rated 500VAC, 700VDC Current Rating 41A	Contact Finish	Silver
Current Rating 41A	Features	Strain Relief
-	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	41A
		Report errors?

#### **CA06COME16-11SB Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **CA06COME16-11SB Payment Methods**



















## **CA06COME16-11SB Shipping Methods**













If you have any question about CA06COME16-11SB, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com