

CA06COME20-11PB

CA06COME20-11PB Information

Heisener.com

Part Number CA06COME20-11PB
Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 13POS INLINE W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CA06COME20-11PB Specifications

Manufacturer Part Number CA06COME20-11PB Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Circular Connectors Circular Connectors Package - Series MIL-DTL-5015, CA-COM-B Connector Type Plug, Male Pins Number of Positions 13 Shell Size - Insert 20-11 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating 22A		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-COM-BConnector TypePlug, Male PinsNumber of Positions13Shell Size - Insert20-11Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated200VAC, 250VDCCurrent Rating22A	Manufacturer Part Number	CA06COME20-11PB
Circular Connectors Package - Series MIL-DTL-5015, CA-COM-B Connector Type Plug, Male Pins Number of Positions 13 Shell Size - Insert 20-11 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Features Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating 22A	Manufacturer	ITT Cannon, LLC
Package - MIL-DTL-5015, CA-COM-B Connector Type Plug, Male Pins Number of Positions 13 Shell Size - Insert 20-11 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating 22A	Category	Connectors, Interconnects
Series MIL-DTL-5015, CA-COM-B Connector Type Plug, Male Pins Number of Positions 13 Shell Size - Insert 20-11 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating 22A		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions13Shell Size - Insert20-11Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated200VAC, 250VDCCurrent Rating22A	Package	-
Number of Positions Shell Size - Insert 20-11 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Features Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating	Series	MIL-DTL-5015, CA-COM-B
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating 22A	Connector Type	Plug, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating 22A	Number of Positions	13
Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating 22A	Shell Size - Insert	20-11
Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating 22A	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating 22A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating 22A	Termination	Solder Cup
Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating 22A	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish Contact Finish Silver Features Strain Relief Voltage - Rated Current Rating Aluminum Alloy, Zinc Die Cast, Nickel Plated Silver Strain Relief 200VAC, 250VDC	Orientation	N (Normal)
Contact Finish Silver Features Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating 22A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating 22A	Shell Material, Finish	Aluminum Alloy, Zinc Die Cast, Nickel Plated
Voltage - Rated 200VAC, 250VDC Current Rating 22A	Contact Finish	Silver
Current Rating 22A	Features	Strain Relief
-	Voltage - Rated	200VAC, 250VDC
Report errors?	Current Rating	22A
		Report errors?

CA06COME20-11PB Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CA06COME20-11PB Payment Methods



















CA06COME20-11PB Shipping Methods













If you have any question about CA06COME20-11PB, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com