



CA06COME20-4SB Information

Heisener.com

Part Number CA06COME20-4SB **Manufacturer** ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 4POS INLINE W/SKTS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CA06COME20-4SB Specifications

Manufacturer Part NumberCA06COME20-4SBManufacturerITT Cannon, LLCCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-COM-BConnector TypePlug, Female SocketsNumber of Positions4Shell Size - Insert20-4Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated900VAC, 1250VDCCurrent Rating41A		
Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-5015, CA-COM-B Connector Type Plug, Female Sockets Number of Positions 4 Shell Size - Insert 20-4 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated Outpack Connectors Circular Connectors Circular Connectors Circular Connectors Connector Type All Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Contact Finish Silver Strain Relief Voltage - Rated Ovoltage - Rated Current Rating 41A	Manufacturer Part Number	CA06COME20-4SB
Circular ConnectorsPackage-SeriesMIL-DTL-5015, CA-COM-BConnector TypePlug, Female SocketsNumber of Positions4Shell Size - Insert20-4Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated900VAC, 1250VDCCurrent Rating41A	Manufacturer	ITT Cannon, LLC
Package - MIL-DTL-5015, CA-COM-B Connector Type Plug, Female Sockets Number of Positions 4 Shell Size - Insert 20-4 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 900VAC, 1250VDC Current Rating 41A	Category	Connectors, Interconnects
Series MIL-DTL-5015, CA-COM-B Connector Type Plug, Female Sockets Number of Positions 4 Shell Size - Insert 20-4 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 900VAC, 1250VDC Current Rating 41A		Circular Connectors
Connector Type Plug, Female Sockets Number of Positions 4 Shell Size - Insert 20-4 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 900VAC, 1250VDC Current Rating 41A	Package	-
Number of Positions Shell Size - Insert 20-4 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 900VAC, 1250VDC Current Rating 41A	Series	MIL-DTL-5015, CA-COM-B
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 900VAC, 1250VDC Current Rating 41A	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 900VAC, 1250VDC Current Rating 41A	Number of Positions	4
Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 900VAC, 1250VDC Current Rating 41A	Shell Size - Insert	20-4
Termination Solder Cup Rastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 900VAC, 1250VDC Current Rating 41A	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 900VAC, 1250VDC Current Rating 41A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Silver Features Strain Relief Voltage - Rated 900VAC, 1250VDC Current Rating 41A	Termination	Solder Cup
Ingress Protection Shell Material, Finish Contact Finish Features Voltage - Rated Current Rating IP67 - Dust Tight, Waterproof Aluminum Alloy, Zinc Die Cast, Nickel Plated Silver Strain Relief 900VAC, 1250VDC 41A	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish Contact Finish Silver Features Strain Relief Voltage - Rated Ourrent Rating Aluminum Alloy, Zinc Die Cast, Nickel Plated Silver Strain Relief 41A	Orientation	N (Normal)
Contact Finish Silver Strain Relief Voltage - Rated Ourrent Rating Silver Strain Relief 41A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features Strain Relief Voltage - Rated 900VAC, 1250VDC Current Rating 41A	Shell Material, Finish	Aluminum Alloy, Zinc Die Cast, Nickel Plated
Voltage - Rated 900VAC, 1250VDC Current Rating 41A	Contact Finish	Silver
Current Rating 41A	Features	Strain Relief
	Voltage - Rated	900VAC, 1250VDC
Report errors?	Current Rating	41A
		Report errors?

CA06COME20-4SB Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CA06COME20-4SB Payment Methods



















CA06COME20-4SB Shipping Methods













If you have any question about CA06COME20-4SB, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com